

SAFETY DATA SHEET

Creation Date 13-Apr-2009

Revision Date 24-Dec-2021

Revision Number 7

1. Identification

Product Name 2-Butanone

Cat No. : AC149670000; AC149670010; AC149670025; AC149670051;
AC149670250; AC149670251

CAS No 78-93-3
Synonyms Methyl ethyl ketone; MEK; Ethyl methyl ketone

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|------------|
| Flammable liquids | Category 2 |
| Serious Eye Damage/Eye Irritation | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Target Organs - Central nervous system (CNS). | |
| Specific target organ toxicity - (repeated exposure) | Category 2 |
| Target Organs - Kidney, Liver. | |

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
 Causes serious eye irritation
 May cause drowsiness or dizziness
 May cause damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Wear protective gloves/protective clothing/eye protection/face protection
 Keep cool

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed
 Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

Other hazards

Contains a known or suspected endocrine disruptor.

3. Composition/Information on Ingredients

| Component | CAS No | Weight % |
|---------------------|---------|----------|
| Methyl ethyl ketone | 78-93-3 | >95 |

4. First-aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

| | |
|--|---|
| | medical attention. |
| Skin Contact | Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if symptoms occur. |
| Inhalation | Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial respiration. |
| Ingestion | Do NOT induce vomiting. Get medical attention. |
| Most important symptoms and effects | Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting |
| Notes to Physician | Treat symptomatically |

5. Fire-fighting measures

| | |
|---|---|
| Suitable Extinguishing Media | CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers. |
| Unsuitable Extinguishing Media | Water may be ineffective |
| Flash Point | -7 °C / 19.4 °F |
| Method - | CC (closed cup) |
| Autoignition Temperature | 404 °C / 759.2 °F |
| Explosion Limits | |
| Upper | 11.4 vol % |
| Lower | 1.4 vol % |
| Oxidizing Properties | Not oxidising |
| Sensitivity to Mechanical Impact | No information available |
| Sensitivity to Static Discharge | No information available |

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

| Health | Flammability | Instability | Physical hazards |
|--------|--------------|-------------|------------------|
| 2 | 3 | 1 | N/A |

6. Accidental release measures

| | |
|---|---|
| Personal Precautions | Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. |
| Environmental Precautions | Avoid release to the environment. See Section 12 for additional Ecological Information. |
| Methods for Containment and Clean Up | Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment. |

7. Handling and storage

| | |
|-----------------|--|
| Handling | Wear personal protective equipment/face protection. Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. |
| Storage. | Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents. Strong acids. Strong bases. Strong reducing agents. Ammonia. copper. Amines. |

8. Exposure controls / personal protection

Exposure Guidelines

| Component | ACGIH TLV | OSHA PEL | NIOSH IDLH | Mexico OEL (TWA) |
|---------------------|-------------------------------|--|--|-------------------------------|
| Methyl ethyl ketone | TWA: 200 ppm STEL: 300 ppm | (Vacated) TWA: 200 ppm (Vacated) TWA: 590 mg/m ³ (Vacated) STEL: 300 ppm (Vacated) STEL: 885 mg/m ³ TWA: 200 ppm TWA: 590 mg/m ³ | IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³ | TWA: 200 ppm STEL: 300 ppm |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

| | |
|-----------------------------|--|
| Engineering Measures | Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. |
|-----------------------------|--|

Personal Protective Equipment

| | |
|---------------------------------|---|
| Eye/face Protection | Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. |
| Skin and body protection | Wear appropriate protective gloves and clothing to prevent skin exposure. |
| Respiratory Protection | Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. |
| Hygiene Measures | Handle in accordance with good industrial hygiene and safety practice. |

9. Physical and chemical properties

| | |
|----------------------------|--------------------------|
| Physical State | Liquid |
| Appearance | Colorless |
| Odor | Characteristic - sweet |
| Odor Threshold | No information available |
| pH | No information available |
| Melting Point/Range | -87 °C / -124.6 °F |
| Boiling Point/Range | 80 °C / 176 °F |
| Flash Point | -7 °C / 19.4 °F |
| Method - | CC (closed cup) |

| | |
|--|--------------------------|
| Evaporation Rate | 3.7 |
| Flammability (solid,gas) | Not applicable |
| Flammability or explosive limits | |
| Upper | 11.4 vol % |
| Lower | 1.4 vol % |
| Vapor Pressure | 105 mbar @ 20 °C |
| Vapor Density | 2.41 |
| Specific Gravity | 0.806 |
| Solubility | Soluble in water |
| Partition coefficient; n-octanol/water | No data available |
| Autoignition Temperature | 404 °C / 759.2 °F |
| Decomposition Temperature | No information available |
| Viscosity | 0.42 mPa.s @ 15°C |
| Molecular Formula | C4 H8 O |
| Molecular Weight | 72.11 |

10. Stability and reactivity

| | |
|---|---|
| Reactive Hazard | None known, based on information available |
| Stability | Hygroscopic. |
| Conditions to Avoid | Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water. |
| Incompatible Materials | Strong oxidizing agents, Strong acids, Strong bases, Strong reducing agents, Ammonia, copper, Amines |
| Hazardous Decomposition Products | Carbon monoxide (CO), Carbon dioxide (CO ₂) |
| Hazardous Polymerization | Hazardous polymerization does not occur. |
| Hazardous Reactions | None under normal processing. |

11. Toxicological information

Acute Toxicity

Product Information Component Information

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|---------------------|---------------------------|------------------------------|------------------------------|
| Methyl ethyl ketone | LD50 = 2483 mg/kg (Rat) | LD50 = 5000 mg/kg (Rabbit) | LC50 = 11700 ppm (Rat) 4 h |

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|------------------------|--|
| Irritation | Irritating to eyes |
| Sensitization | No information available |
| Carcinogenicity | The table below indicates whether each agency has listed any ingredient as a carcinogen. |

| Component | CAS No | IARC | NTP | ACGIH | OSHA | Mexico |
|---------------------|---------|------------|------------|------------|------------|------------|
| Methyl ethyl ketone | 78-93-3 | Not listed | Not listed | Not listed | Not listed | Not listed |

Mutagenic Effects Not mutagenic in AMES Test

Reproductive Effects No information available.

Developmental Effects No information available.

| | |
|---|---|
| Teratogenicity | No information available. |
| STOT - single exposure | Central nervous system (CNS) |
| STOT - repeated exposure | Kidney Liver |
| Aspiration hazard | No information available |
| Symptoms / effects, both acute and delayed | Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting |
| Endocrine Disruptor Information | No information available |
| Other Adverse Effects | The toxicological properties have not been fully investigated. |

12. Ecological information

Ecotoxicity

| Component | Freshwater Algae | Freshwater Fish | Microtox | Water Flea |
|---------------------|------------------|--|---|--|
| Methyl ethyl ketone | Not listed | Lepomis macrochirus: LC50=3,22 g/L 96 h | EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min | EC50: = 5091 mg/L, 48h (Daphnia magna) EC50: 4025 - 6440 mg/L, 48h Static (Daphnia magna) EC50: > 520 mg/L, 48h (Daphnia magna) |

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

| Component | log Pow |
|---------------------|---------|
| Methyl ethyl ketone | 0.29 |

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

| Component | RCRA - U Series Wastes | RCRA - P Series Wastes |
|-------------------------------|------------------------|------------------------|
| Methyl ethyl ketone - 78-93-3 | U159 | - |

14. Transport information

DOT

| | |
|-----------------------------|---------------------|
| UN-No | UN1193 |
| Proper Shipping Name | Ethyl methyl ketone |
| Hazard Class | 3 |
| Packing Group | II |

TDG

| | |
|-----------------------------|---------------------|
| UN-No | UN1193 |
| Proper Shipping Name | ETHYL METHYL KETONE |
| Hazard Class | 3 |
| Packing Group | II |

IATA

| | |
|-----------------------------|---------------------|
| UN-No | UN1193 |
| Proper Shipping Name | Methyl ethyl ketone |
| Hazard Class | 3 |

Reportable Quantity (RQ): Y
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

| Component | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|---------------------|---|---|---|
| Methyl ethyl ketone | - | Use restricted. See item 75. (see link for restriction details) | - |

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

| Component | CAS No | OECD HPV | Persistent Organic Pollutant | Ozone Depletion Potential | Restriction of Hazardous Substances (RoHS) |
|---------------------|---------|----------|------------------------------|---------------------------|--|
| Methyl ethyl ketone | 78-93-3 | Listed | Not applicable | Not applicable | Not applicable |

| Component | CAS No | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements | Rotterdam Convention (PIC) | Basel Convention (Hazardous Waste) |
|---------------------|---------|---|--|----------------------------|------------------------------------|
| Methyl ethyl ketone | 78-93-3 | Not applicable | Not applicable | Not applicable | Annex I - Y42 |

16. Other information

Prepared By Regulatory Affairs
 Thermo Fisher Scientific
 Email: EMSDS.RA@thermofisher.com

Creation Date 13-Apr-2009
Revision Date 24-Dec-2021
Print Date 24-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS