

# SAFETY DATA SHEET

Creation Date 27-Apr-2009

Revision Date 24-Dec-2021

**Revision Number** 9

1. Identification				
Product Name Methanol				
Cat No. : A947-4; A947POP-200; A947RS-115; A947RS-200; A947RS- A947SS-115; A947SS-200; A947SS-28; A947SS-50; XXA947 XXA947ETU200LI;				
CAS No Synonyms	67-56-1 Methyl alcohol			
Recommended UseLaboratory chemicals.Uses advised against.				

## Details of the supplier of the safety data sheet

<u>Company</u> Fisher Scientific Company One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

**Emergency Telephone Number** 

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

## 2. Hazard(s) identification

## **Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Acute oral toxicity	Category 3
Acute dermal toxicity	Category 3
Acute Inhalation Toxicity - Vapors	Category 3
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Optic nerve, Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Kidney, Liver, spleen, Blood.	

## Label Elements

Signal Word Danger

#### **Hazard Statements**

Highly flammable liquid and vapor Causes damage to organs Causes damage to organs through prolonged or repeated exposure Toxic if swallowed, in contact with skin or if inhaled



#### Precautionary Statements Prevention

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

# Keep cool

Response

IF exposed: Call a POISON CENTER or doctor/physician

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician

#### Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Rinse mouth

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

#### Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### Disposal

Dispose of contents/container to an approved waste disposal plant **Hazards not otherwise classified (HNOC)** 

#### Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS. WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

## 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Methyl alcohol	67-56-1	>95

4. First-aid measures				
General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.				
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.			
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.			
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.			
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.			
Most important symptoms and effects Notes to Physician	Difficulty in breathing. May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting Treat symptomatically			

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point	9.7 °C / 49.5 °F
Method -	No information available
Autoignition Temperature	455 °C / 851 °F
Explosion Limits Upper Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	31.00 vol % 6.0 vol % t No information available No information available

### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

## **Hazardous Combustion Products**

Carbon monoxide (CO). Formaldehyde.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

<u>NFPA</u> Health 1	Flammability 3	Instability 0	Physical hazards N/A
	6. Accidental re	lease measures	
Personal Precautions	Evacuate personnel to safe	e areas. Keep people away fro	m and upwind of spill/leak. Use

Environmental Precautions	personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Should not be released into the environment. See Section 12 for additional Ecological Information.		
Methods for Containment and Clear Up	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.		
	7. Handling and storage		
Handling	Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.		
Storage.	Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammables area. Incompatible Materials. Strong oxidizing agents. Strong acids. Acid anhydrides. Acid chlorides. Strong bases. Metals. Peroxides.		

8. Exposure controls / personal protection

## Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m <sup>3</sup> (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m <sup>3</sup> Skin TWA: 200 ppm	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 250 ppm
		TWA: 260 mg/m <sup>3</sup>		

## <u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstatic location.	
Personal Protective Equipment		
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.	
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.	
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.	
Hygiene Measures	When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.	

#### **Methanol**

	<b>J</b>
Physical State	Liquid
Appearance	Colorless
Odor	Alcohol-like
Odor Threshold	No information available
рН	Not applicable
Melting Point/Range	-98 °C / -144.4 °F
Boiling Point/Range	64.7 °C/148.5 °F @ 760 mmHg
Flash Point	9.7 °C / 49.5 °F
Evaporation Rate	5.2 (ether = 1)
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	31.00 vol %
Lower	6.0 vol %
Vapor Pressure	128 hPa @ 20 °C
Vapor Density	1.11
Specific Gravity	0.791
Solubility	Miscible with water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	455 °C / 851 °F
Decomposition Temperature	No information available
Viscosity	0.55 cP at 20 °C
Molecular Formula	C H4 O
Molecular Weight	32.04
VOC Content(%)	100
Surface tension	0.02255 N/m @ 20°C

# 9. Physical and chemical properties

## **Reactive Hazard** None known, based on information available Stability Stable under normal conditions. **Conditions to Avoid** Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition. Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides, Strong bases, **Incompatible Materials** Metals, Peroxides Hazardous Decomposition Products Carbon monoxide (CO), Formaldehyde **Hazardous Polymerization** Hazardous polymerization does not occur. **Hazardous Reactions** None under normal processing. 11. Toxicological information

10. Stability and reactivity

## Acute Toxicity

#### **Product Information** Component Information

Component information							
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation				
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L ( Rat ) 4 h				
oxicologically Synergistic Carbon tetrachloride							
Products							
Delayed and immediate effects as well as chronic effects from short and long-term exposure							
Irritation	May cause skin and eye in	ritation					
Sensitization	No information available						

## Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Methyl alcohol			NTP	ACGIH	OSHA	Mexico	
<b>,</b>	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed	
Mutagenic Effects		No information available					
Reproductive Effects		No information available.					
Developmental Effects		Component substance is listed on California Proposition 65 as a developmental hazard.					
Teratogenicity		No information available.					
STOT - single exposure		Optic nerve Central nervous system (CNS)					
STOT - repeated exposure		Kidney Liver spleen Blood					
Aspiration hazard		No information available					
Symptoms / effects,l delayed	both acute and	May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting					
Endocrine Disruptor	Information	No information available					
Other Adverse Effects		The toxicological properties have not been fully investigated.					

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	
			EC50 = 43000 mg/L 5 min	
Persistence and Degrada	bility Persistence	is unlikely based on inform	ation available.	
<b>Bioaccumulation/Accum</b>	ulation No information	on available.		
Mobility Will likely be mobile in		mobile in the environment	due to its volatility.	
Component			log Pow	
1	Methyl alcohol		-0.74	

# 13. Disposal considerations

Waste Disposal Methods

Should not be released into the environment.

1	Component	RCRA - U Series Wastes	RCRA - P Series Wastes
	Methyl alcohol - 67-56-1	U154	-

	14. Transport information
DOT	
UN-No	UN1230
Proper Shipping Name	METHANOL
Hazard Class	3
Packing Group	II
TDG	
UN-No	UN1230
Proper Shipping Name	METHANOL
Hazard Class	3
Subsidiary Hazard Class	6.1
-	

Packing Group IATA	Ш
UN-No Proper Shipping Name	UN1230 METHANOL
Hazard Class	3
Subsidiary Hazard Class	6.1
Packing Group	II
IMDG/IMO	
UN-No	UN1230
Proper Shipping Name	METHANOL
Hazard Class	3
Subsidiary Hazard Class	6.1
Packing Group	II
	15 Pog

## 15. Regulatory information

## United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Methyl alcohol	67-56-1	Х	ACTIVE	-

#### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710) X - Listed

'-' - Not Listed

## TSCA 12(b) - Notices of Export Not applicable

#### International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Methyl alcohol	67-56-1	Х	-	200-659-6	Х	Х	Х	Х	Х	KE-23193

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### U.S. Federal Regulations

## SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	Х		-

**OSHA** - Occupational Safety and Not applicable Health Administration

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Methyl alcohol	67-56-1	Developmental	-	Developmental

## U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl alcohol	Х	Х	Х	Х	Х

## U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

#### Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	<b>U</b> (
Methyl alcohol	-	Use restricted. See item 69. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable
Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable

	16. Other information
Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date Revision Date Print Date Revision Summary	27-Apr-2009 24-Dec-2021 24-Dec-2021 This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

