

SAFETY DATA SHEET

Creation Date 28-Apr-2009 Revision Date 29-Mar-2024 Revision Number 4

1. Identification

Product Name Acetone

Cat No. : 19392

CAS No 67-64-1 Synonyms 2-Propanone

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill. MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids
Category 2
Serious Eye Damage/Eye Irritation
Category 2
Specific target organ toxicity (single exposure)
Category 3
Target Organs - Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure) Category 2

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor Causes serious eye irritation May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eve irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Acetone	67-64-1	>95

4. First-aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

Revision Date 29-Mar-2024 Acetone

call a physician.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Clean mouth with water and drink afterwards plenty of water. Ingestion

Most important symptoms and

effects

Notes to Physician

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema

Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point -20 °C / -4 °F

Method -CC (closed cup)

Autoignition Temperature 465 °C / 869 °F

Explosion Limits

Upper 12.8 vol % Lower 2.5 vol % **Oxidizing Properties** Not oxidising

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Formaldehyde. Methanol.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health **Flammability** Instability Physical hazards 2 3 N/A

Accidental release measures

Personal Precautions Use personal protective equipment as required. Ensure adequate ventilation. Remove all

sources of ignition. Take precautionary measures against static discharges.

Should not be released into the environment. **Environmental Precautions**

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Up

7. Handling and storage

Handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid

ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents. Strong reducing agents. Strong bases. Peroxides. Halogenated compounds. Alkali metals. Amines.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Acetone	TWA: 250 ppm	(Vacated) TWA: 750 ppm	IDLH: 2500 ppm	TWA: 500 ppm
	STEL: 500 ppm	(Vacated) TWA: 1800 mg/m ³	TWA: 250 ppm	STEL: 750 ppm
		(Vacated) STEL: 2400	TWA: 590 mg/m ³	
		mg/m³	_	
		(Vacated) STEL: 1000 ppm		
		TWA: 1000 ppm		
		TWA: 2400 mg/m ³		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations

and safety showers are close to the workstation location. Use explosion-proof

electrical/ventilating/lighting equipment.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: low boiling organic solvent. Type AX. Brown. conforming to EN371.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorsweetOdor Threshold19.8 ppmpH7

 Melting Point/Range
 -95 °C / -139 °F

 Boiling Point/Range
 56 °C / 132.8 °F

 Flash Point
 -20 °C / -4 °F

 Method CC (closed cup)

Method -CC (closed cup)Evaporation Rate5.6 (Butyl Acetate = 1.0)Flammability (solid,gas)Not applicable

Flammability or explosive limits

 Upper
 12.8 vol %

 Lower
 2.5 vol %

Vapor Pressure 247 mbar @ 20 °C

Vapor Density2.0Specific Gravity0.790

SolubilitySoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature465 °C / 869 °F

Decomposition Temperature > 4°C

Viscosity 0.32 mPa.s @ 20 °C

 Molecular Formula
 C3 H6 O

 Molecular Weight
 58.08

 VOC Content(%)
 100

 Refractive index
 1.358 - 1.359

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Heat, flames and sparks. Incompatible products. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong reducing agents, Strong bases, Peroxides, Halogenated

compounds, Alkali metals, Amines

Hazardous Decomposition Products Carbon monoxide (CO₂), Formaldehyde, Methanol

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component LD50 O		LD50 Oral	LD50 Dermal	LC50 Inhalation
	Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit)	76 mg/l, 4 h, (rat)
			> 7400 mg/kg (rat)	

Toxicologically SynergisticCarbon tetrachloride; Chloroform; Trichloroethylene; Bromodichloromethane;
Products
Carbon tetrachloride; Chloroform; Trichloroethylene; Bromodichloromethane;
Dibromochloromethane; N-nitrosodimethylamine; 1,1,2-Trichloroethane; Styrene;

Acetonitrile, 2,5-Hexanedione; Ethanol; 1,2-Dichlorobenzene

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Acetone	67-64-1	Not listed				

Mutagenic Effects No information available

Reproductive Effects

No information available.

Developmental Effects

No information available.

Revision Date 29-Mar-2024 Acetone

Teratogenicity No information available.

Central nervous system (CNS) STOT - single exposure

STOT - repeated exposure None known

No information available **Aspiration hazard**

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting:

May cause pulmonary edema

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	NOEC = 430 mg/l (algae; 96	Oncorhynchus mykiss: LC50	EC50 = 14500 mg/L/15 min	EC50 = 8800 mg/L/48h
	h)	= 5540 mg/l 96h	_	EC50 = 12700 mg/L/48h
		Alburnus alburnus: LC50 =		EC50 = 12600 mg/L/48h
		11000 mg/l 96h		
		Leuciscus idus: LC50 =		
		11300 mg/L/48h		
		Salmo gairdneri: LC50 =		
		6100 mg/L/24h		

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Acetone	-0.24

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acetone - 67-64-1	U002	-

14. Transport information

DOT

UN1090 **UN-No Proper Shipping Name ACETONE**

Hazard Class 3 **Packing Group** Ш

TDG

UN-No UN1090 **Proper Shipping Name ACETONE**

Hazard Class 3 **Packing Group** Ш

IATA

UN1090 **UN-No Proper Shipping Name ACETONE**

Hazard Class

Packing Group

IMDG/IMO

UN-No UN1090
Proper Shipping Name ACETONE
Hazard Class 3

Ш

Packing Group

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Acetone	67-64-1	Х	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Acetone	67-64-1	Χ	-	200-662-2	Х	Χ	Х	Χ	Х	KE-29367

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and Not applicable

Health Administration

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
-----------	-----------------------------	---	-------------------------------

Revision Date 29-Mar-2024

Acetone

Acetone	5000 lb	-	5000 lb
			2270 kg

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acetone	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

This product does not contain any DHS chemicals.

Security

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
		Annex XIV - Substances	Annex XVII - Restrictions	1907/2006) article 59 -
		Subject to Authorization	on Certain Dangerous	Candidate List of
			Substances	Substances of Very High
				Concern (SVHC)
Acetone	67-64-1	-	Use restricted. See item	-
			75.	
			(see link for restriction	
			details)	

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

	Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ī	Acetone	67-64-1	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - (2012/18/EC) - Qualifying Quantities		Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
		for Major Accident	for Safety Report		
		Notification	Requirements		
Acetone	67-64-1	Not applicable	Not applicable	Not applicable	Annex I - Y42

16. Other information

Prepared By Health, Safety and Environmental Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

 Creation Date
 28-Apr-2009

 Revision Date
 29-Mar-2024

 Print Date
 29-Mar-2024

Revision Summary New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS