

# **SAFETY DATA SHEET**

Creation Date 26-Sep-2009 Revision Date 29-Mar-2024 Revision Number 6

# 1. Identification

Product Name Acrylic acid

Cat No.: 43359

**CAS No** 79-10-7

Synonyms Acrylic acid, inhibited; 2-Propenoic acid; Acroleic acid

Recommended Use Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

# Details of the supplier of the safety data sheet

# Company

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill. MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757

#### **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

# 2. Hazard(s) identification

# Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Acute oral toxicity

Category 4

Acute dermal toxicity

Category 4

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Target Organs - Respiratory system.

# Label Elements

# Signal Word

Danger

#### **Hazard Statements**

Flammable liquid and vapor Causes severe skin burns and eye damage May cause respiratory irritation Harmful if swallowed, in contact with skin or if inhaled



## **Precautionary Statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

# Response

Immediately call a POISON CENTER or doctor/physician

# Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Skin

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

# Ingestion

Rinse mouth

Do NOT induce vomiting

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### Disposa

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Very toxic to aquatic life

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Acrylic acid	79-10-7	>95
4-Methoxyphenol	150-76-5	0.018-0.022

# 4. First-aid measures

**Eye Contact**Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Immediate medical attention is required.

**Inhalation** Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Difficulty in breathing. Causes burns by all exposure routes. . Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe

damage to the delicate tissue and danger of perforation

Notes to Physician Treat symptomatically

# 5. Fire-fighting measures

Suitable Extinguishing Media Carbon dioxide (CO 2). Dry chemical. Water mist may be used to cool closed containers.

Chemical foam. Water mist may be used to cool closed containers.

Unsuitable Extinguishing Media No information available

**Flash Point** 48 °C / 118.4 °F

Method - No information available

Autoignition Temperature 374 °C / 705.2 °F

**Explosion Limits** 

**Upper** 8.0 vol % **Lower** 2.0 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

# **Specific Hazards Arising from the Chemical**

Flammable. Corrosive material. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Vapors may form explosive mixtures with air. Do not allow run-off from fire-fighting to enter drains or water courses.

# **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2).

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

HealthFlammabilityInstabilityPhysical hazards322N/A

# 6. Accidental release measures

Personal Precautions Wear self-contained breathing apparatus and protective suit. Evacuate personnel to safe

areas. Remove all sources of ignition. Do not get in eyes, on skin, or on clothing. Take

Revision Date 29-Mar-2024 Acrylic acid

# **Environmental Precautions**

precautionary measures against static discharges.

Do not flush into surface water or sanitary sewer system. Do not allow material to

contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. See Section 12 for additional

Ecological Information. Avoid release to the environment. Collect spillage.

Up

Methods for Containment and Clean Wear self-contained breathing apparatus and protective suit. Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

# 7. Handling and storage

#### Handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/yapors/spray, Do not ingest. If swallowed then seek immediate medical assistance. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only non-sparking tools.

#### Storage.

Keep at temperatures between 15 °C and 25 °C. Keep away from heat, sparks and flame. Store indoors. May form explosive peroxides. Regularly check inhibitor levels to maintain peroxide levels below 1%. Keep container tightly closed in a dry and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Strong bases. oxygen. Peroxides. Halogens. Aldehydes. Amines. Acid anhydrides.

# 8. Exposure controls / personal protection

# **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Acrylic acid	TWA: 2 ppm	(Vacated) TWA: 10 ppm	TWA: 2 ppm	TWA: 2 ppm
-	Skin	(Vacated) TWA: 30 mg/m <sup>3</sup>	TWA: 6 mg/m <sup>3</sup>	
		Skin	_	
4-Methoxyphenol	TWA: 5 mg/m <sup>3</sup>	(Vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>

# Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

#### **Engineering Measures**

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

# **Personal Protective Equipment**

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection** 

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Organic gases and vapours filter. Type A. Brown. conforming to EN14387. **Recommended Filter type:** 

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorStench

Odor Threshold No information available

**pH** 1.0-2

Melting Point/Range 13 °C / 55.4 °F

Boiling Point/Range 139 °C / 282.2 °F @ 760 mmHg

Flash Point 48 °C / 118.4 °F Evaporation Rate No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 8.0 vol %

 Lower
 2.0 vol %

 Vapor Pressure
 @ 3.8 mbar °C 20

 Vapor Density
 2.48 (Air = 1.0)

Specific Gravity 1.050

SolubilityNo information availablePartition coefficient; n-octanol/waterNo data availableAutoignition Temperature374 °C / 705.2 °FDecomposition TemperatureNo information availableViscosity1.3 mPa s at 20 °C

Molecular Formula C3 H4 O2 Molecular Weight 72.06

# 10. Stability and reactivity

Reactive Hazard Yes

Stability Hazardous polymerization may occur. May form explosive peroxides on prolonged storage.

Hygroscopic.

Conditions to Avoid Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure

to light. Exposure to moist air or water. Incompatible products.

Incompatible Materials Strong oxidizing agents, Strong bases, oxygen, Peroxides, Halogens, Aldehydes, Amines,

Acid anhydrides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization may occur upon depletion of inhibitor.

**Hazardous Reactions** None under normal processing.

# 11. Toxicological information

**Acute Toxicity** 

Product Information Harmful by inhalation, in contact with skin and if swallowed Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acrylic acid	468-1500 mg/kg (Rat)	>2000 mg/kg (Rabbit)	>5.1 mg/L/4h (Rat)
4-Methoxyphenol	1600 mg/kg (Rat)	LD50 > 2000 mg/kg ( Rabbit )	Not listed

**Toxicologically Synergistic** 

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Causes burns by all exposure routes

Revision Date 29-Mar-2024 Acrylic acid

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Acrylic acid	79-10-7	Not listed				
4-Methoxyphenol	150-76-5	Not listed				

**Mutagenic Effects** No information available

**Reproductive Effects** Experiments have shown reproductive toxicity effects on laboratory animals.

**Developmental Effects** No information available. **Teratogenicity** No information available.

STOT - single exposure Respiratory system STOT - repeated exposure None known

**Aspiration hazard** No information available

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes

severe swelling, severe damage to the delicate tissue and danger of perforation

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** See actual entry in RTECS for complete information.

# 12. Ecological information

#### **Ecotoxicity**

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acrylic acid	EC50: = 0.17 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: = 0.04 mg/L, 72h (Desmodesmus subspicatus)	LC50: = 222 mg/L, 96h semi-static (Brachydanio rerio)	Not listed	EC50: = 95 mg/L, 48h (Daphnia magna)
4-Methoxyphenol	Not listed	LC50: = 28.5 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 84.3 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 3.66 mg/L 5 min EC50 = 4.30 mg/L 15 min EC50 = 4.61 mg/L 30 min	Not listed

**Persistence and Degradability** Miscible with water Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

. Will likely be mobile in the environment due to its water solubility. **Mobility** 

Component	log Pow
Acrylic acid	0.46
4-Methoxyphenol	1.3

# 13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and

national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acrylic acid - 79-10-7	U008	-

# 14. Transport information

DOT

UN-No UN2218

Proper Shipping Name ACRYLIC ACID, STABILIZED

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

TDG\_

UN-No UN2218

Proper Shipping Name ACRYLIC ACID, STABILIZED

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group || |

<u>IATA</u>

UN-No UN2218

Proper Shipping Name ACRYLIC ACID, STABILIZED

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN2218

Proper Shipping Name ACRYLIC ACID, STABILIZED

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group || |

# 15. Regulatory information

#### **United States of America Inventory**

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Acrylic acid	79-10-7	Χ	ACTIVE	-
4-Methoxyphenol	150-76-5	X	ACTIVE	-

# Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

# **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Acrylic acid	79-10-7	Х	-	201-177-9	Х	Χ	Х	Х	Χ	KE-29442
4-Methoxyphenol	150-76-5	Х	-	205-769-8	Х	Χ	Х	Х	Х	KE-23353

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

# U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting threasholds
Acrylic acid	79-10-7	>95	1.0 %	-

# SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)** 

Not applicable

#### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Acrylic acid	X		-

**OSHA** - Occupational Safety and

Not applicable

Health Administration

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Acrylic acid	5000 lb	-	5000 lb 2270 kg

**California Proposition 65** 

This product does not contain any Proposition 65 chemicals.

# U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acrylic acid	X	X	X	X	X
4-Methoxyphenol	X	X	X	-	X

# **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant Y
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

## Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
·		Annex XIV - Substances	Annex XVII - Restrictions	1907/2006) article 59 -

		Subject to Authorization	on Certain Dangerous Substances	Candidate List of Substances of Very High Concern (SVHC)
Acrylic acid	79-10-7	-	Use restricted. See item 75. (see link for restriction details)	-
4-Methoxyphenol	150-76-5	-	Use restricted. See item 75. (see link for restriction details)	-

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

# Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Acrylic acid	79-10-7	Listed	Not applicable	Not applicable	Not applicable
4-Methoxyphenol	150-76-5	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

# Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities	(2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
		for Major Accident Notification	for Safety Report Requirements		
Acrylic acid	79-10-7	Not applicable	Not applicable	Not applicable	Annex I - Y34
4-Methoxyphenol	150-76-5	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information
-----------------------

Prepared By Health, Safety and Environmental Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

 Creation Date
 26-Sep-2009

 Revision Date
 29-Mar-2024

 Print Date
 29-Mar-2024

**Revision Summary** New emergency telephone response service provider.

# Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**