

# **SAFETY DATA SHEET**

Creation Date 21-Jan-2009 Revision Date 29-Mar-2024 Revision Number 4

# 1. Identification

Product Name 1-Butanol

Cat No. : L13171

**CAS No** 71-36-3

Synonyms n-Butanol; n-Butyl alcohol, Butan-1-ol

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

## Details of the supplier of the safety data sheet

## Company

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill. MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757

#### **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

# 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids
Category 3
Acute oral toxicity
Category 4
Skin Corrosion/Irritation
Category 2
Serious Eye Damage/Eye Irritation
Category 1
Specific target organ toxicity (single exposure)
Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

#### Label Elements

# Signal Word

Danger

#### **Hazard Statements**

Flammable liquid and vapor Harmful if swallowed

Causes skin irritation
Causes serious eye damage
May cause respiratory irritation
May cause drowsiness or dizziness



#### **Precautionary Statements**

## Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

#### Response

Get medical attention/advice if you feel unwell

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

#### Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

# Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

#### **Disposal**

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

None identified

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
n-Butyl alcohol	71-36-3	99

## 4. First-aid measures

**General Advice** If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and

effects

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting
Treat symptomatically

Notes to Physician

# 5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable Extinguishing Media No information available

Flash Point 35 °C / 95 °F

Method - CC (closed cup)

Autoignition Temperature 340 °C / 644 °F

**Explosion Limits** 

**Upper** 11.2 vol % **Lower** 1.4 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

#### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

## **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2).

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

HealthFlammabilityInstabilityPhysical hazards230N/A

## 6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Ensure adequate ventilation.

**Environmental Precautions** Should not be released into the environment.

**Methods for Containment and Clean** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up** 

7. Handling and storage

Handling Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not

get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents. Reducing Agent. Acid chlorides. copper. Copper alloys. Acid anhydrides.

# 8. Exposure controls / personal protection

#### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
n-Butyl alcohol	n-Butyl alcohol TWA: 20 ppm		IDLH: 1400 ppm	TWA: 20 ppm
		(Vacated) Ceiling: 50 ppm	Ceiling: 50 ppm	
		(Vacated) Ceiling: 150 Ceiling: 150 mg/m <sup>3</sup>		
		mg/m³		
		TWA: 100 ppm		
		TWA: 300 mg/m <sup>3</sup>		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

**Personal Protective Equipment** 

**Eve/face Protection**Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended Filter type:** Organic gases and vapours filter. Type A. Brown. conforming to EN14387.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorAlcohol-like

Odor Threshold No information available

pH No information available
Melting Point/Range -89 °C / -128.2 °F
Boiling Point/Range 117.6 °C / 243.7 °F
Flash Point 35 °C / 95 °F

Method - CC (closed cup)
Evaporation Rate 0.46

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 11.2 vol %

 Lower
 1.4 vol %

Vapor Pressure 6.7 mbar @ 20 °C

Vapor Density 2.6 Specific Gravity 0.810

SolubilitySlightly soluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature340 °C / 644 °FDecomposition TemperatureNo information availableViscosity2.95 mPa.s (20 °C)

Molecular FormulaC4 H10 OMolecular Weight74.12Refractive index1.390 - 1.400

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

**Conditions to Avoid** Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

Incompatible Materials Strong oxidizing agents, Reducing Agent, Acid chlorides, copper, Copper alloys, Acid

anhydrides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions**None under normal processing.

# 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

**Component Information** 

Component LD50 Oral		LD50 Dermal	LC50 Inhalation		
n-Butyl alcohol	LD50 = 700 mg/kg (Rat)	LD50 = 3402 mg/kg ( Rabbit )	LC50 > 8000 ppm (Rat) 4 h		

**Toxicologically Synergistic** 

**Products** 

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Severe eye irritant; Irritating to respiratory system and skin

Sensitization No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
n-Butyl alcohol	71-36-3	Not listed				

Mutagenic Effects No information available

Reproductive Effects

No information available.

Developmental Effects

No information available.

**Teratogenicity** No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

delayed

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

# 12. Ecological information

#### **Ecotoxicity**

Do not flush into surface water or sanitary sewer system.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
n-Butyl alcohol	EC50: 225 mg/L, 96h	LC50: 1376 mg/L, 96h	EC50 = 2041.4 mg/L 5 min	EC50: 1328 mg/L, 48h
	(Pseudokirchneriella	(Pimephales promelas)	EC50 = 2186 mg/L 30 min	(Daphnia magna) OECD
	subcapitata) OECD	OECD Guideline 203 :	EC50 = 3980 mg/L 24 h	Guideline 202
	Guideline 201	100000 - 500000 μg/L, 96h	EC50 = 4400 mg/L 17 h	EC50: 1897 - 2072 mg/L,
	EC50: > 500 mg/L, 72h	static (Lepomis macrochirus)	_	48h Static (Daphnia magna)
	(Desmodesmus	LC50: = 1740 mg/L, 96h		EC50: = 1983 mg/L, 48h
	subspicatus)	flow-through (Pimephales		(Daphnia magna)
	EC50: > 500 mg/L, 96h	promelas)		
	(Desmodesmus	LC50: = 1910000 µg/L, 96h		
	subspicatus)	static (Pimephales		
		promelas)		
		LC50: 1730 - 1910 mg/L,		
		96h static (Pimephales		
		promelas)		

Persistence and Degradability Soluble in water Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** . Will likely be mobile in the environment due to its water solubility.

Component	log Pow
n-Butyl alcohol	1

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes	
n-Butvl alcohol - 71-36-3	U031	-	

# 14. Transport information

DOT

UN-No UN1120
Proper Shipping Name BUTANOLS

Hazard Class 3
Packing Group III

TDG

UN-No UN1120 Proper Shipping Name BUTANOLS

Hazard Class 3
Packing Group III

Revision Date 29-Mar-2024 1-Butanol

IATA

UN1120 **UN-No Proper Shipping Name BUTANOLS** 

**Hazard Class Packing Group** Ш

IMDG/IMO

**UN-No** UN1120 **BUTANOLS Proper Shipping Name** 

**Hazard Class** Ш **Packing Group** 

# 15. Regulatory information

#### **United States of America Inventory**

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
n-Butyl alcohol	71-36-3	X	ACTIVE	-

#### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed '-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT) Not applicable

TSCA 12(b) - Notices of Export

Not applicable

#### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
n-Butyl alcohol	71-36-3	Χ	-	200-751-6	Χ	Χ	Χ	Х	Х	KE-03867

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

## U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting threasholds	
n-Butyl alcohol	71-36-3	99	1.0 %	-	

#### SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)** Not applicable

Clean Air Act Not applicable

**OSHA** - Occupational Safety and

Health Administration

Not applicable

## **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
n-Butyl alcohol	5000 lb	-	5000 lb 2270 kg

**California Proposition 65** 

This product does not contain any Proposition 65 chemicals.

# U.S. State Right-to-Know Regulations

	Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
I	n-Butyl alcohol	X	X	X	-	X

**U.S. Department of Transportation** 

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous	REACH Regulation (EC 1907/2006) article 59 - Candidate List of
			J	Substances of Very High Concern (SVHC)
n-Butyl alcohol	71-36-3	-	Use restricted. See item 75. (see link for restriction details)	-

## **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
n-Butyl alcohol	71-36-3	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

## Other International Regulations

Component	CAS No	Seveso III Directive	Seveso III Directive	Rotterdam	Basel Convention

			(2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Convention (PIC)	(Hazardous Waste)
n-Butyl alcohol	71-36-3	Not applicable	Not applicable	Not applicable	Not applicable

# 16. Other information

Prepared By Health, Safety and Environmental Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

 Creation Date
 21-Jan-2009

 Revision Date
 29-Mar-2024

 Print Date
 29-Mar-2024

**Revision Summary** New emergency telephone response service provider.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**