

# SAFETY DATA SHEET

Creation Date 06-Nov-2009

Revision Date 02-May-2024

Revision Number 6

1. Identification

**Product Name** 

Petroleum ether 40/60

## Cat No. : L14649

CAS No Synonyms 64742-49-0 Ligroine

Recommended Use Uses advised against

Laboratory chemicals. Food, drug, pesticide or biocidal product use.

## Details of the supplier of the safety data sheet

## <u>Company</u>

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill, MA 01835-8099 Tel: 800-343-0660 Fax: 800-322-4757

## **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## 2. Hazard(s) identification

## **Classification**

ſ

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	
Aspiration Toxicity	Category 1
	5 <i>7</i>

## Label Elements

**Signal Word** Danger

## Hazard Statements

Highly flammable liquid and vapor May be fatal if swallowed and enters airways May cause drowsiness or dizziness Causes skin irritation Causes serious eye irritation



#### Precautionary Statements Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting equipment Use only non-sparking tools Take precautionary measures against static discharge Keep cool Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell Skin If skin irritation occurs: Get medical advice/attention IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse Eves IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention Ingestion IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

## Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

## Disposal

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

## 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Hydrocarbons, C6, isoalkanes < 5% n-hexane	64742-49-0	<100
(Iso-Hexane)		
Hexane	110-54-3	-

## 4. First-aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Most important symptoms and effects	Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	CO <sub>2</sub> , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective, Do not use a solid water stream as it may scatter and spread fire
Flash Point	-45 °C / -49 °F
Method -	No information available
Autoignition Temperature	230 °C / 446 °F
Explosion Limits Upper Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	No data available No data available It No information available No information available

## Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

## **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

<u>NFPA</u>	Health 3	Flammability 3	<b>Instability</b> 0	Physical hazards N/A	
	6. Accidental release measures				
Persona	l Precautions	Use personal protective eq sources of ignition. Take pr	uipment as required. Ensure ac ecautionary measures against	dequate ventilation. Remove all static discharges.	
Environ	mental Precautions		ater or sanitary sewer system.	0	

Methods for Containment and CleanSoak up with inert absorbent material. Keep in suitable, closed containers for disposal.UpRemove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

	7. Handling and storage
Handling	Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
Storage.	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents.

	8. Exposure controls / personal protection
Exposure Guidelines	This product does not contain any hazardous materials with occupational e

This product does not contain any hazardous materials with occupational exposure limitsestablished by the region specific regulatory bodies.

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Hexane	TWA: 50 ppm	(Vacated) TWA: 50 ppm	IDLH: 1100 ppm	TWA: 50 ppm
	Skin	(Vacated) TWA: 180 mg/m <sup>3</sup>		
		TWA: 500 ppm	TWA: 180 mg/m <sup>3</sup>	
		TWA: 1800 mg/m <sup>3</sup>		

## <u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.	
Personal Protective Equipment		
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Tight sealing safety goggles. Face protection shield.	
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.	
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.	
Recommended Filter type:	low boiling organic solvent. Type AX. Brown. conforming to EN371.	
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.	

9. Physical and chemical properties				
Physical State	Liquid			
Appearance	Colorless			
Odor	Petroleum distillates			
Odor Threshold	No information available			
рН	No information available			
Melting Point/Range	No data available			

Boiling Point/Range Flash Point Evaporation Rate Flammability (solid,gas) Flammability or explosive limits Upper Lower Vapor Pressure Vapor Density Specific Gravity Solubility Partition coefficient; n-octanol/water Autoignition Temperature Decomposition Temperature Viscosity 40 - 70 °C / 104 - 158 °F -45 °C / -49 °F 13 (Butyl acetate = 1.0) Not applicable

No data available No data available 23 hPa @ 20 °C >1 @ 101 kPa 0.65 Insoluble in water No data available 230 °C / 446 °F No information available 0.45 mm2/s at 25 °C (ASTM D445)

## 10. Stability and reactivity

Reactive Hazard	None known, based on information available	
Stability	Stable under normal conditions.	
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.	
Incompatible Materials	Strong oxidizing agents	
Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)		
Hazardous Polymerization	Hazardous polymerization does not occur.	
Hazardous Reactions	None under normal processing.	

11. Toxicological information

## Acute Toxicity

Dermal LD50

Vapor LC50

Product Information	
Oral LD50	

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information			-			
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation			
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	LD50 > 5000 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit)	LC50 = 73680 ppm (Rat) 4 h			
Hexane	LD50 = 25 g/kg (Rat)	LD50 = 25 g/kg (Rat) LD50 = 3000 mg/kg (Rabbit) LC50 = 48000 ppr				
Toxicologically Synergistic	No information available	·	*			
Products Delayed and immediate effects Irritation	as well as chronic effects fror	n short and long-term exposur	<u>e</u>			
Sensitization	No information available					
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carc The classification as a carcinogen need not apply if the full refining history is know can be shown that the substance from which it is produced is not a carcinogen. Th applies only to certain complex oil derived substances in Annex I.					

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico

Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	64742-49-0	Not listed	Not listed	Not listed	Not listed	Not listed		
Hexane	110-54-3	Not listed	Not listed	Not listed	Not listed	Not listed		
Mutagenic Effects		No information ava	ailable					
Reproductive Effects	5	California Proposition 65. Product is or contains a chemical which is a known or suspected reproductive hazard.						
Developmental Effect	ts	No information ava	ailable.					
Teratogenicity		No information available.						
STOT - single expos STOT - repeated exp		Central nervous system (CNS) None known						
Aspiration hazard		Category 1						
Symptoms / effects,both acute and delayed		<b>d</b> Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting						
Endocrine Disruptor	Information	No information available						
Other Adverse Effec	ts	The toxicological properties have not been fully investigated.						

# 12. Ecological information

## Ecotoxicity

The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	Not listed	LC50: = 8.41 mg/L, 96h semi-static, closed (Oncorhynchus mykiss)	Not listed	Not listed
Hexane	Not listed	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	Not listed	EC50: 3.87 mg/L/48h
Persistence and Degrada	stence and Degradability Persistence		ation available.	·
Bioaccumulation/ Accum	ulation No inform	ation available.		
Mobility	Will likely	Will likely be mobile in the environment due to its volatility.		

Component	log Pow
Hexane	4.11

	13. Disposal considerations
Waste Disposal Methods	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.
	14. Transport information

	14. Transport information			
DOT				
UN-No	UN1268			
Proper Shipping Name Petroleum distillates, n.o.s.				
Hazard Class 3				
Packing Group	П			

- <u>TDG</u> UN-No	UN1268
Proper Shipping Name Hazard Class	Petroleum distillates, n.o.s. 3
Packing Group	3 II
IATA	
UN-No	UN1268
Proper Shipping Name	Petroleum distillates, n.o.s.
Hazard Class	3
Packing Group	II
IMDG/IMO	
UN-No	UN1268
Proper Shipping Name	Petroleum distillates, n.o.s.
Hazard Class	3
Packing Group	II
	15. Regulatory information

## United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Hydrocarbons, C6, isoalkanes <	64742-49-0	Х	ACTIVE	-
5% n-hexane (Iso-Hexane)				
Hexane	110-54-3	Х	ACTIVE	-

#### Legend:

**TSCA** US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710) X - Listed

'-' - Not Listed

# TSCA - Per 40 CFR 751, Regulation of Certain Chemical Not applicable Substances & Mixtures, Under TSCA Section 6(h) (PBT)

TSCA 12(b) - Notices of Export

Not applicable

## International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Hydrocarbons, C6, isoalkanes <	64742-49-0	Х	-	265-151-9	Х	-		Х	Х	KE-25623
5% n-hexane (Iso-Hexane)										
Hexane	110-54-3	Х	-	203-777-6	Х	Х	Х	Х	Х	KE-18626

**KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

## U.S. Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting threasholds
Hexane	110-54-3	-	1.0 %	-

## SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

#### CWA (Clean Water Act) Not applicable

Clean Air Act	Not applicable

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Hexane	Х		-

**OSHA** - Occupational Safety and Not applicable Health Administration

### CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Hexane	5000 lb	-	5000 lb 2270 kg

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Hexane	110-54-3	Male Reproductive	-	Developmental
U.S. State Right-to-Know	Not applicable	e		

## Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Hexane	Х	Х	Х	Х	Х

## U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	N
DOT Severe Marine Pollutant	Ν

U.S. Department of Homeland This product does not contain any DHS chemicals. Security

## Other International Regulations

Mexico - Grade Severe risk, Grade 4

## Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	64742-49-0	-	Use restricted. See item 28. (see link for restriction details) Use restricted. See item 29. (see link for restriction details) Use restricted. See item 75.	<u>-</u>

			(see link for restriction details)	
Hexane	110-54-3	-	Use restricted. See item	-
			75.	
			(see link for restriction	
			details)	

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	64742-49-0	Listed	Not applicable	Not applicable	Not applicable
Hexane	110-54-3	Listed	Not applicable	Not applicable	Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

#### **Other International Regulations**

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)		Not applicable	Not applicable	Not applicable	Not applicable
Hexane	110-54-3	Not applicable	Not applicable	Not applicable	Annex I - Y42

## 16. Other information

Prepared By

Health, Safety and Environmental Department Email: chem.techinfo@thermofisher.com www.thermofisher.com

Creation Date	06-Nov-2009
Revision Date	02-May-2024
Print Date	02-May-2024
Revision Summary	New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# **End of SDS**