

SAFETY DATA SHEET

Creation Date 25-Jun-2009 Revision Date 24-Dec-2021 Revision Number 6

1. Identification

Product Name Sodium methoxide, 5.4M (30 wt.%) solution in methanol

Cat No.: AC168600000; AC168600010; AC168600025; AC168600100;

AC168600250; AC168600251

Synonyms Sodium methylate

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 3 Corrosive to metals Category 1 Acute oral toxicity Category 3 Category 3 Acute dermal toxicity Acute Inhalation Toxicity - Vapors Category 3 Skin Corrosion/Irritation Category 1 A Serious Eye Damage/Eye Irritation Category 1 Specific target organ toxicity (single exposure) Category 1

Target Organs - Central nervous system (CNS), Optic nerve.

Label Elements

Signal Word

Danger

Hazard Statements

Flammable liquid and vapor

May be corrosive to metals

Causes severe skin burns and eye damage

May cause respiratory irritation

May cause drowsiness or dizziness

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure

Toxic if swallowed, in contact with skin or if inhaled



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep only in original container

Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Ingestion

Rinse mouth

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Spills

Absorb spillage to prevent material damage

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Store in corrosive resistant polypropylene container with a resistant inliner

Store in a dry place

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Reacts violently with water

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS. WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Methyl alcohol	67-56-1	70
Sodium methoxide	124-41-4	30

4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim

ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh

air. Immediate medical attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue

and danger of perforation

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media DO NOT USE WATER

Flash Point 33 °C / 91.4 °F

Method - No information available

Autoignition Temperature 240 °C / 464 °F

Explosion Limits

Upper 44 vol % **Lower** 5.50 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition can lead to release of irritating gases and vapors. Sodium oxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NI		п	
IV	г	г	А

Health	Flammability	Instability	Physical hazards
3	3	1	W

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Storage.

Keep away from water or moist air. Keep away from heat, sparks and flame. Store indoors. Flammables area. Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Acids.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm	TWA: 200 ppm
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m ³	TWA: 200 ppm	STEL: 250 ppm
	Skin	(Vacated) STEL: 250 ppm	TWA: 260 mg/m ³	
		(Vacated) STEL: 325 mg/m ³	STEL: 250 ppm	
		Skin	STEL: 325 mg/m ³	
		TWA: 200 ppm	_	
		TWA: 260 mg/m ³		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Use only under a chemical fume hood. Ensure that evewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166. Tight sealing safety goggles. Face protection shield.

Wear appropriate protective gloves and clothing to prevent skin exposure. Skin and body protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection**

> EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid **Appearance** Light yellow Alcohol-like Odor

No information available **Odor Threshold**

Ha Not applicable

1 - 5 °C / 33.8 - 41 °F Melting Point/Range

Boiling Point/Range 93 °C / 199.4 °F @ 760 mmHg

Flash Point 33 °C / 91.4 °F **Evaporation Rate** No information available

Flammability (solid, gas) Not applicable

Flammability or explosive limits

44 vol % Upper Lower 5.50 vol %

150 hPa @ 50 °C **Vapor Pressure Vapor Density** No information available

Specific Gravity 0.97

Solubility Water reactive Partition coefficient; n-octanol/water No data available **Autoignition Temperature** 240 °C / 464 °F **Decomposition Temperature** No information available

No information available **Viscosity**

10. Stability and reactivity

Reactive Hazard Yes

Moisture sensitive. Stability

Conditions to Avoid Exposure to moist air or water. Keep away from open flames, hot surfaces and sources of

ignition. Exposure to moisture.

Incompatible Materials Strong oxidizing agents, Acids

Hazardous Decomposition Products Carbon monoxide (CO₂), Carbon dioxide (CO₂), Thermal decomposition can lead to release

of irritating gases and vapors, Sodium oxides

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions Reacts violently with water.

11. Toxicological information

Acute Toxicity

Product Information

Category 3. ATE = 50 - 300 mg/kg. Oral LD50 **Dermal LD50** Category 3. ATE = 200 - 1000 mg/kg.

Vapor LC50 Based on ATE data, the classification criteria are not met. ATE > 20 mg/l. Category 3. ATE

= 2 - 10 mg/l.

Component Information

Component LD50 Oral		LD50 Dermal	LC50 Inhalation		
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h		
Sodium methoxide	1687 mg/kg (Rat)	>2000 mg/kg (Rat)	Not listed		

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Causes burns by all exposure routes

Sensitization No information available

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

Component CAS No		IARC NTP		ACGIH	OSHA	Mexico	
Methyl alcohol	67-56-1	Not listed					
Sodium methoxide	124-41-4	Not listed					

Mutagenic Effects No information available

California Proposition 65. Reproductive toxicity. **Reproductive Effects**

Developmental Effects No information available. **Teratogenicity** No information available.

Central nervous system (CNS) Optic nerve STOT - single exposure

STOT - repeated exposure None known

Aspiration hazard No information available

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	_
			EC50 = 43000 mg/L 5 min	

Persistence is unlikely based on information available. Persistence and Degradability

Bioaccumulation/ Accumulation No information available.

. Is not likely mobile in the environment. **Mobility**

Component	log Pow

Sodium methoxide, 5.4M (30 wt.%) solution in methanol

Methyl alcohol	-0.74
Sodium methoxide	-0.75

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes		
Methyl alcohol - 67-56-1	U154	-		

14. Transport information

DOT

UN-No UN1289

Proper Shipping Name SODIUM METHYLATE SOLUTIONS

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group III

TDG

UN-No UN1289

Proper Shipping Name SODIUM METHYLATE SOLUTION

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group III

<u>IATA</u>

UN-No UN1289

Proper Shipping Name SODIUM METHYLATE SOLUTION

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group III

IMDG/IMO

UN-No UN1289

Proper Shipping Name SODIUM METHYLATE SOLUTION

Hazard Class 3 Subsidiary Hazard Class 8 Packing Group III

15. Regulatory information

United States of America Inventory

Component	CAS No TSC		TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Methyl alcohol	67-56-1	X	ACTIVE	-
Sodium methoxide	124-41-4	Χ	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL

Sodium methoxide, 5.4M (30 wt.%) solution in methanol

Methyl alcohol	67-56-1	Χ	-	200-659-6	Χ	Χ	Χ	Χ	Χ	KE-23193
Sodium methoxide	124-41-4	Х	-	204-699-5	Χ	Х	Х	Х	Х	KE-23196

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	70	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Sodium methoxide	X	1000 lb	-	-

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

	Component	Hazardous Substances RQs	CERCLA EHS RQs
Γ	Methyl alcohol	5000 lb	-
Γ	Sodium methoxide	1000 lb	-

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component CAS No		California Prop. 65	Prop 65 NSRL	Category	
Methyl alcohol	67-56-1	Developmental	-	Developmental	

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl alcohol	X	X	X	X	X
Sodium methoxide	Х	Х	Х	-	-

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

L	Component	REACH (1907/2006) - Annex XIV -	REACH (1907/2006) - Annex XVII -	REACH Regulation (EC

	Substances Subject to Authorization	Restrictions on Certain Dangerous Substances	1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	-	Use restricted. See item 69.	-
		(see link for restriction details)	
Sodium methoxide	-	Use restricted. See item 75.	-
		(see link for restriction details)	

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable
Sodium methoxide	124-41-4	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable
Sodium methoxide	124-41-4	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 25-Jun-2009

 Revision Date
 24-Dec-2021

 Print Date
 24-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS