

SAFETY DATA SHEET

Creation Date 13-Oct-2009 Revision Date 24-Dec-2021 Revision Number 6

1. Identification

Product Name Ethyl acetate

Cat No.: AC268350000; AC268350010; AC268350025; AC268350040

CAS No 141-78-6

Synonyms Acetic acid ethyl ester

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Serious Eye Damage/Eye Irritation

Category 2

Specific target organ toxicity (single exposure)

Category 3

Target Organs - Central nervous system (CNS).

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor Causes serious eye irritation May cause drowsiness or dizziness

•



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Ethyl acetate	141-78-6	>95

4. First-aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin ContactWash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

•

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and

effects

Difficulty in breathing. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea

and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable Extinguishing Media Water may be ineffective, Do not use a solid water stream as it may scatter and spread fire

Flash Point -4 °C / 24.8 °F

Method - CC (closed cup)

Autoignition Temperature 427 °C / 800.6 °F

Explosion Limits

Upper 11.5 vol %
Lower 2.0 vol %
Oxidizing Properties Not oxidising

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Fiammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

HealthFlammabilityInstabilityPhysical hazards230N/A

6. Accidental release measures

Personal Precautions
Environmental Precautions

Use personal protective equipment as required. Ensure adequate ventilation.

Should not be released into the environment. See Section 12 for additional Ecological

Information.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up**

7. Handling and storage

Handling Ensure adequate ventilation. Wear personal protective equipment/face protection. Do not

get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

Storage. Flammables area. Keep away from heat, sparks and flame. Keep container tightly closed in

a dry and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Strong acids. Amines. Peroxides.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl acetate	TWA: 400 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm	TWA: 400 ppm
		(Vacated) TWA: 1400 mg/m ³	TWA: 400 ppm	
		TWA: 400 ppm	TWA: 1400 mg/m ³	
		TWA: 1400 mg/m ³	_	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

Eve/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory ProtectionNo protective equipment is needed under normal use conditions.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorsweetOdor Threshold50 ppm

pH No information available Melting Point/Range -83.5 °C / -118.3 °F

Boiling Point/Range 75 - 78 °C / 167 - 172.4 °F

Flash Point -4 °C / 24.8 °F CC (closed cup)

Evaporation Rate 6.2

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 11.5 vol %

 Lower
 2.0 vol %

 Vapor Pressure
 103 mbar @ 20°C

Vapor Pressure

Vapor Density 3.04 Specific Gravity 0.902

Solubility
Slightly soluble in water
Partition coefficient; n-octanol/water
Autoignition Temperature
Slightly soluble in water
No data available
427 °C / 800.6 °F

Decomposition TemperatureNo information availableViscosity0.45 cP @ 20 °C

Molecular Formula C4 H8 O2
Molecular Weight 88.11

Revision Date 24-Dec-2021 Ethyl acetate

Surface tension 24 mN/m @ 20°C

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stable under normal conditions. Stability

Conditions to Avoid Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Amines, Peroxides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl acetate	10,200 mg/kg (Rat)	> 20 mL/kg(Rabbit) > 18000 mg/kg(Rabbit)	58 mg/l (rat; 8 h)

Toxicologically Synergistic

No information available

Products

Teratogenicity

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl acetate	141-78-6	Not listed				

Mutagenic Effects No information available

Reproductive Effects No information available. No information available. **Developmental Effects**

Central nervous system (CNS) STOT - single exposure

STOT - repeated exposure None known

No information available **Aspiration hazard**

delayed

Symptoms / effects, both acute and May cause central nervous system depression: Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

No information available.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl acetate	EC50 = 3300 mg/L/48h	Fathead minnow: LC50: 230	EC50 = 1180 mg/L 5 min	EC50 = 717 mg/L/48h
		mg/l/ 96h	EC50 = 1500 mg/L 15 min	_
		Gold orfe: LC50: 270	EC50 = 5870 mg/L 15 min	
		mg/L/48h	EC50 = 7400 mg/L 2 h	

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl acetate	0.6

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Ethyl acetate - 141-78-6	U112	-

14. Transport information

DOT

UN-No UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3
Packing Group ||

TDG

UN-No UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3
Packing Group ||

IATA

UN-No UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1173

Proper Shipping Name ETHYL ACETATE

Hazard Class 3
Packing Group

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Ethyl acetate	141-78-6	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Ethyl acetate	141-78-6	X	-	205-500-4	X	X	X	Х	X	KE-00047

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethyl acetate	5000 lb	-

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl acetate	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component		REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
Ethyl acetate	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl acetate	141-78-6	Listed	Not applicable	Not applicable	Not applicable
Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl acetate	141-78-6	Not applicable	Not applicable	Not applicable	Annex I - Y42

 ,	\sim 1.1		4.4
 6	Other	intorm	nation
U.		1111(7111	16111011

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 13-Oct-2009

 Revision Date
 24-Dec-2021

 Print Date
 24-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS