

SAFETY DATA SHEET

Creation Date 11-Jun-2009 Revision Date 24-Dec-2021 Revision Number 6

1. Identification

Product Name Toluene

Cat No.: AC268370000; AC268370010; AC268370025

CAS No 108-88-3

Synonyms Tol; Methylbenzene

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2 Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2 Reproductive Toxicity Category 2 Specific target organ toxicity (single exposure) Category 3 Target Organs - Respiratory system, Central nervous system (CNS). Specific target organ toxicity - (repeated exposure) Category 2 Target Organs - Kidney, Liver, spleen, Blood, Neurological effects, Eyes, Ears. Aspiration Toxicity Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor May be fatal if swallowed and enters airways Causes skin irritation Causes serious eye irritation May cause drowsiness or dizziness Suspected of damaging the unborn child

May cause damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Toluene	108-88-3	<=100

4. First-aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur. Risk of serious damage to the lungs (by aspiration).

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call

a physician or poison control center immediately. If vomiting occurs naturally, have victim

lean forward.

Most important symptoms and

effects

Notes to Physician

. Causes central nervous system depression: Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point 4 °C / 39.2 °F

Method - No information available

Autoignition Temperature 535 °C / 995 °F

Explosion Limits

Upper 7.1 vol %
Lower 1.1 vol %
Oxidizing Properties Not oxidising

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health **Flammability** Instability Physical hazards N/A

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents. Strong acids. Strong bases. Halogenated compounds.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm	IDLH: 500 ppm	TWA: 20 ppm
		(Vacated) TWA: 375 mg/m ³	TWA: 100 ppm	
		Ceiling: 300 ppm	TWA: 375 mg/m ³	
		(Vacated) STEL: 150 ppm	STEL: 150 ppm	
		(Vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³	
		TWA: 200 ppm	-	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdoraromaticOdor Threshold1.74 ppm

pH No information available

 Melting Point/Range
 -95 °C / -139 °F

 Boiling Point/Range
 111 °C / 231.8 °F @ 760 mmHg

 Flash Point
 4 °C / 39.2 °F

 Evaporation Rate
 2.4 (Butyl acetate = 1.0)

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 7.1 vol %

 Lower
 1.1 vol %

 Vapor Pressure
 29 mbar @ 20 °C

Vapor Density 3.1 Specific Gravity 0.866

SolubilityInsoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature535 °C / 995 °FDecomposition TemperatureNo information availableViscosity0.6 mPa.s @ 20 °C

Molecular Formula C7 H8
Molecular Weight 92.14

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Strong bases, Halogenated compounds

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information
Component

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

Toxicologically Synergistic

Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes, respiratory system and skin

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Toluene	108-88-3	Not listed				

Mutagenic Effects Not mutagenic in AMES Test

Experiments have shown reproductive toxicity effects on laboratory animals. **Reproductive Effects**

Developmental Effects Developmental effects have occurred in experimental animals.

Teratogenicity Possible risk of harm to the unborn child.

STOT - single exposure Respiratory system Central nervous system (CNS) Kidney Liver spleen Blood Neurological effects Eyes Ears STOT - repeated exposure

Aspiration hazard No information available

delayed

Symptoms / effects,both acute and Causes central nervous system depression: Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Toluene	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50 = 19.7 mg/L 30 min	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)
	subcapitata)	g		

Persistence and Degradability Persistence is unlikely

Bioaccumulation/ Accumulation No information available.

Is not likely mobile in the environment due its low water solubility. **Mobility**

Component	log Pow
Toluene	2.7

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Toluene - 108-88-3	U220	-

14. Transport information

DOT

UN1294 **UN-No TOLUENE Proper Shipping Name**

Hazard Class 3 **Packing Group** Ш

TDG

UN1294 **UN-No Proper Shipping Name TOLUENE**

Hazard Class Packing Group Ш

IATA

UN1294 **UN-No TOLUENE Proper Shipping Name**

Hazard Class Packing Group Ш

IMDG/IMO

UN1294 **UN-No Proper Shipping Name TOLUENE**

Hazard Class Packing Group Ш

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Toluene	108-88-3	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Toluene	108-88-3	Χ	-	203-625-9	Χ	Х	Χ	Χ	Χ	KE-33936

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	<=100	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

	Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	
Γ	Toluene	X	1000 lb	X	X	

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Toluene	X		-

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs	
Toluene	1000 lb 1 lb	-	

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Toluene 108-88-3		Developmental	-	Developmental

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Toluene	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Component

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	, ,	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
Toluene	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	- 1

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No

			Pollutant	Potential	Hazardous Substances (RoHS)
Toluene	108-88-3	Listed	Not applicable	Not applicable	Not applicable
					_
Component	CAS No	Seveso III Directive (2012/18/EC) - (2012/18/ Qualifying Quantities Qualifying Q for Major Accident for Safety Notification Requiren		Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Toluene	108-88-3	Not applicable	Not applicable	Not applicable	Annex I - Y42

Persistent Organic

Ozone Depletion

Restriction of

OECD HPV

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 11-Jun-2009

 Revision Date
 24-Dec-2021

 Print Date
 24-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS