

SAFETY DATA SHEET

Creation Date 19-May-2009

Revision Date 26-Dec-2021

Revision Number 7

1. Identification		
Product Name	Tebbe reagent, 0.5M solution in toluene	
Cat No. :	AC426060000; AC426061000	
Synonyms	Bis(cyclopentadienyl-delta-chloro(dimethylaluminium-delta-methylenetitanium	
Recommended Use Uses advised against	Laboratory chemicals. Food, drug, pesticide or biocidal product use.	
Details of the supplier of the safe	ty data sheet	
<u>Company</u> Fisher Scientific Company One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100	Acros Organics One Reagent Lane Fair Lawn, NJ 07410	
Emergency Telephone Number	For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11	

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2	
Skin Corrosion/Irritation	Category 1 B	
Serious Eye Damage/Eye Irritation	Category 1	
Reproductive Toxicity	Category 2	
Specific target organ toxicity (single exposure)	Category 3	
Target Organs - Respiratory system, Central nervous sys	tem (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2	
Target Organs - Neurological effects, Eyes, Ears.		
Aspiration Toxicity	Category 1	

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor

May be fatal if swallowed and enters airways

Causes severe skin burns and eye damage

May cause respiratory irritation

May cause drowsiness or dizziness

Suspected of damaging the unborn child

May cause damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Ingestion

Do NOT induce vomiting

Rinse mouth

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

3.	Composition/Information on	Ingredients

Component	CAS No	Weight %

Toluene	108-88-3	85
Titanium,	67719-69-1	15
.muchlorobis(.eta.5-2,4-cyclopentadien-1-yl)(dimet		
hylaluminum)mumethylene-		

4. First-aid measures		
General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.	
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.	
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.	
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).	
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.	
Most important symptoms and effects	Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation	
Notes to Physician	Treat symptomatically	
	5. Fire-fighting measures	

Suitable Extinguishing Media	CO 2, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	No information available
Flash Point	4 °C / 39.2 °F
Method -	No information available
Autoignition Temperature Explosion Limits	No information available
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impac	t No information available

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen chloride gas.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

<u>NFPA</u>	Health 3	Flammability 3	Instability 1	Physical hazards N/A
		6. Accidental rel	lease measures	
Personal	Precautions	personnel to safe areas. Ke	uipment as required. Ensure a eep people away from and upv recautionary measures against	vind of spill/leak. Remove all
Environn	nental Precautions		ater or sanitary sewer system.	
Methods Up	for Containment and C	lean Soak up with inert absorber Remove all sources of ignit	nt material. Keep in suitable, c tion. Use spark-proof tools and	
		7. Handling a	and storage	
Handling		Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Handle under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.		
Storage.		nitrogen. Store in freezer. S	Store under an inert atmospher	r, sparks and flame. Keep under re. Protect from moisture. Keep place. Incompatible Materials.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm	IDLH: 500 ppm	TWA: 20 ppm
		(Vacated) TWA: 375 mg/m ³	TWA: 100 ppm	
		Ceiling: 300 ppm	TWA: 375 mg/m ³	
		(Vacated) STEL: 150 ppm	STEL: 150 ppm	
		(Vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³	
		TWA: 200 ppm	_	

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

	· · · · ·
Physical State	Liquid
Appearance	Dark red Purple
Odor	No information available
Odor Threshold	No information available
рН	Not applicable
Melting Point/Range	No data available
Boiling Point/Range	No information available
Flash Point	4 °C / 39.2 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	0.927
Solubility	Reacts with water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C13 H18 AI CI Ti
Molecular Weight	284.62

10. Stability and reactivity

Reactive Hazard	None known, based on information available	
Stability	Moisture sensitive. Air sensitive.	
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moisture. Exposure to air. Exposure to moist air or water.	
Incompatible Materials	Strong oxidizing agents	
Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen chloride gas		
Hazardous Polymerization	Hazardous polymerization does not occur.	
Hazardous Reactions	None under normal processing.	

11. Toxicological information

Acute Toxicity

Product Information					
Oral LD50	Based on ATE data, the cl	assification criteria are not met. A	ATE > 2000 mg/kg.		
Dermal LD50		assification criteria are not met. A			
Vapor LC50	Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.				
Component Information					
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		

Toluene		> 5000 mg/kg (Ra	it) 1200	0 mg/kg (Rabbit)	26700 pj	om (Rat)1 h			
Toxicologically Syn Products Delayed and immed	-		No information available s well as chronic effects from short and long-term exposure						
Irritation		Causes burns by	Causes burns by all exposure routes						
Sensitization		No information av	No information available						
Carcinogenicity		The table below i	The table below indicates whether each agency has listed any ingredient as a carcinog						
Component	CAS N	o IARC	NTP	ACGIH	OSHA	Mexico			
Toluene	108-88-		Not listed	Not listed	Not listed	Not listed			
Titanium, .muchlorobis(.eta.5-2 ,4-cyclopentadien-1-yl) (dimethylaluminum)m umethylene-			Not listed	Not listed	Not listed	Not listed			
Mutagenic Effects		No information available							
Reproductive Effect			No information available.						
Teratogenicity		Possible risk of h	arm to the unborn c	hild.					
STOT - single expos STOT - repeated exp			Respiratory system Central nervous system (CNS) Neurological effects Eyes Ears						
Aspiration hazard		No information av	No information available						
Symptoms / effects delayed	s,both acute	tiredness, nausea emesis is contrain investigated: Inge	d Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation						
Endocrine Disrupto	r Informatio	on No information av	ailable						
Other Adverse Effect	cts	The toxicological	properties have not	been fully investig	gated.				

12. Ecological information

Ecotoxicity The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms. Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Toluene	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella		EC50 = 19.7 mg/L 30 min	EC50: = 11.5 mg/L, 48h (Daphnia magna)
	subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)	15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h		EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)
Persistence and Degrad	ability Persistence	is unlikely		•
Bioaccumulation/ Accumulation No information av		tion available.		

. Is not likely mobile in the environment.

Component log Pow		
	Component	log Pow

Toluene	2.7

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Toluene - 108-88-3	U220	-

14. Transport information DOT UN-No UN2924 **Proper Shipping Name** Flammable liquid, corrosive, n.o.s. **Hazard Class** 3 **Subsidiary Hazard Class** 8 Packing Group Ш TDG **UN-No** UN2924 **Proper Shipping Name** Flammable liquid, corrosive, n.o.s. Hazard Class 3 **Subsidiary Hazard Class** 8 **Packing Group** Ш ΙΑΤΑ UN2924 **UN-No Proper Shipping Name** Flammable liquid, corrosive, n.o.s. **Hazard Class** 3 **Subsidiary Hazard Class** 8 **Packing Group** Ш IMDG/IMO UN-No UN2924 **Proper Shipping Name** Flammable liquid, corrosive, n.o.s. **Technical Name** Toluene, Bis(cyclopentadienyl-delta-chloro(dimethylaluminium-delta-methylenetitanium Hazard Class 3 **Subsidiary Hazard Class** 8 **Packing Group** Ш

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Toluene	108-88-3	Х	ACTIVE	-
Titanium, .muchlorobis(.eta.5-2,4-cyclopent adien-1-yl)(dimethylaluminum)mu methylene-		-	-	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710) X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

X = listed, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Toluene	108-88-3	Х	-	203-625-9	Х	Х	Х	Х	Х	KE-33936
Titanium, .muchlorobis(.eta.5-2,4-cyclopent adien-1-yl)(dimethylaluminum)mu methylene-		-	-	-	-	-		-	-	-

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	85	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Com	oonent	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Tol	uene	X	1000 lb	Х	Х

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Toluene	Х		-

OSHA - Occupational Safety and Not applicable Health Administration

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Toluene	1000 lb 1 lb	-

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category		
Toluene	108-88-3	Developmental	-	Developmental		
IIS State Dight to Know						

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Toluene	Х	Х	Х	Х	Х

U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	N
DOT Severe Marine Pollutant	N

Ν

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	_

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Toluene	108-88-3	Listed	Not applicable	Not applicable	Not applicable
Titanium,	67719-69-1	Not applicable	Not applicable	Not applicable	Not applicable
.muchlorobis(.eta.5-2,4-cyclo					
pentadien-1-yl)(dimethylalumi					
num)mumethylene-					

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Toluene	108-88-3	Not applicable	Not applicable	Not applicable	Annex I - Y42
Titanium, .muchlorobis(.eta.5-2,4-cyclo pentadien-1-yl)(dimethylalumi num)mumethylene-	67719-69-1	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By

Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com

Creation Date Revision Date Print Date Revision Summary 19-May-2009 26-Dec-2021 26-Dec-2021 This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS