

SAFETY DATA SHEET

Creation Date 19-May-2009

Revision Date 23-Feb-2022

Revision Number 6

1. Identification

Product Name	3-Methoxyphenylmagnesium bromide, 1M solution in THF/toluene
Cat No. :	AC426750000; AC426751000; AC426758000
Synonyms	No information available
Recommended Use Uses advised against	Laboratory chemicals. Food, drug, pesticide or biocidal product use.
Details of the supplier of the safet	y data sheet

<u>Company</u>	
Fisher Scientific Company	Acros Organics
One Reagent Lane	One Reagent Lane
Fair Lawn, NJ 07410	Fair Lawn, NJ 07410
Tel: (201) 796-7100	

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

Emergency Telephone Number

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Skin Corrosion/Irritation	Category 1 B
Serious Eye Damage/Eye Irritation	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (C	NS).
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Kidney, Liver, Heart, spleen, Blood, Neurologic	al effects, Eyes, Ears.
Aspiration Toxicity	Category 1

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor May be fatal if swallowed and enters airways Causes severe skin burns and eye damage May cause respiratory irritation May cause drowsiness or dizziness Suspected of causing cancer Suspected of damaging the unborn child May cause damage to organs through prolonged or repeated exposure



Precautionary Statements Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting equipment Use only non-sparking tools Take precautionary measures against static discharge Keep cool Response Immediately call a POISON CENTER or doctor/physician Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Skin IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse Eves IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Ingestion Do NOT induce vomiting Rinse mouth Fire In case of fire: Use CO2, dry chemical, or foam for extinction Storage Store locked up Store in a well-ventilated place. Keep container tightly closed Disposal Dispose of contents/container to an approved waste disposal plant Hazards not otherwise classified (HNOC) Reacts violently with water May form explosive peroxides WARNING. Cancer and Reproductive Harm - https://www.p65warnings.ca.gov/.

3. Composition/Information on Ingredients

Component		CAS No	Weight %
Toluene		108-88-3	50-60
Tetrahydrofuran		109-99-9 36282-40-3	20-30
3-Methoxyphenylmagnesium	3-Methoxyphenylmagnesium bromide		20
	4.	First-aid measures	
General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention required.		nce. Immediate medical attention is
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minute Immediate medical attention is required.		he eyelids, for at least 15 minutes.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.		
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respirati with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).		d the substance; give artificial respiration way valve or other proper respiratory
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control cen immediately. If vomiting occurs naturally, have victim lean forward.		Call a physician or poison control center
Most important symptoms and effects	Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastr lavage or emesis is contraindicated. Possible perforation of stomach or esophagus sho be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous syste depression		is a corrosive material. Use of gastric ration of stomach or esophagus should severe damage to the delicate tissue concentrations may cause symptoms
Notes to Physician	Treat sympto	omatically	
	5. Fi	re-fighting measures	
Suitable Extinguishing Media	CO 2, dry che closed conta	emical, dry sand, alcohol-resistant foan iners.	n. Water mist may be used to cool
Unsuitable Extinguishing Media	DO NOT US	E WATER	
Flash Point	No information	on available °C / °F	
Method -	No information available		

Autoignition TemperatureNo information availableExplosion LimitsNo data availableUpperNo data availableLowerNo data availableSensitivity to Mechanical ImpactNo information availableSensitivity to Static DischargeNo information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Magnesium oxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

<u>NFPA</u>	A Health Flammability 3 3		Instability 2	Physical hazards W
		6. Accidental rel	ease measures	
Personal	Precautions	personnel to safe areas. Ke sources of ignition. Take pr	eep people away from and up ecautionary measures agains	t static discharges.
Environm	nental Precautions	Do not flush into surface wa	ater or sanitary sewer system.	
Methods Up	for Containment and C		emove all sources of ignition.	closed containers for disposal. Do Use spark-proof tools and
		7. Handling a	and storage	
Handling		clothing. Use only under a ingest. If swallowed then se water. If peroxide formation open flames, hot surfaces ignition of vapors by static	chemical fume hood. Do not be eek immediate medical assistant is suspected, do not open or and sources of ignition. Use o	not get in eyes, on skin, or on preathe mist/vapors/spray. Do not ance. Do not allow contact with move container. Keep away from nly non-sparking tools. To avoid parts of the equipment must be ischarges.
Storage.		cool and well-ventilated pla water or moist air. Shelf life storage. Containers should of peroxides. Should crysta and the product should be	ce. Keep away from heat, spa 12 months. May form explos be dated when opened and t ils form in a peroxidizable liqu considered extremely danger	p containers tightly closed in a dry, arks and flame. Keep away from ive peroxides on prolonged ested periodically for the presence id, peroxidation may have occurred bus. In this instance, the container sives area. Incompatible Materials.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm	IDLH: 500 ppm	TWA: 20 ppm
		(Vacated) TWA: 375 mg/m ³	TWA: 100 ppm	
		Ceiling: 300 ppm	TWA: 375 mg/m ³	
		(Vacated) STEL: 150 ppm	STEL: 150 ppm	
		(Vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³	
		TWA: 200 ppm	-	
Tetrahydrofuran	TWA: 50 ppm	(Vacated) TWA: 200 ppm	IDLH: 2000 ppm	TWA: 200 ppm
	STEL: 100 ppm	(Vacated) TWA: 590 mg/m ³	TWA: 200 ppm	TWA: 590 mg/m ³
	Skin	(Vacated) STEL: 250 ppm	TWA: 590 mg/m ³	STEL: 250 ppm
		(Vacated) STEL: 735 mg/m ³	STEL: 250 ppm	STEL: 735 mg/m ³
		TWA: 200 ppm	STEL: 735 mg/m ³	
		TWA: 590 mg/m ³	-	

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Tan
Odor	No information available
Odor Threshold	No information available
рН	No information available
Melting Point/Range	No data available
Boiling Point/Range	No information available
Flash Point	No information available °C / °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	1
Solubility	Immiscible
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available

10. Stability and reactivity

Reactive Hazard	Yes
Stability	Moisture sensitive. Air sensitive. Reacts violently with water.
Conditions to Avoid	Incompatible products. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water. Exposure to air. Exposure to moisture.
Incompatible Materials	Strong oxidizing agents

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO₂), Magnesium oxides

lazardous Polymer	ization	Hazardous polymerization does not occur.				
lazardous Reactio	IS	None under normal processing. Reacts violently with water.				
		11. Toxicol	ogical info	ormation		
Cute Toxicity						
Product Information Dral LD50 Dermal LD50 /apor LC50 Component Informa		No acute toxicity information is available for this product Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.				
Componer		LD50 Oral		LD50 Dermal	LC50	Inhalation
Toluene		> 5000 mg/kg (Rat)	LD50 = 1	2000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h	
Tetrahydrofu	ran	1650 mg/kg(Rat)	> 20	00 mg/kg (Rabbit)	180 mg/L (Rat)1 h 53.9 mg/L (Rat)4 h	
Toxicologically Syn Products Delayed and immed	-	No information available as chronic effects from short and long-term exposure				
		Causes burns by all exposure routes				
rritation		Causes burns by all	exposure routes			
rritation Sensitization		Causes burns by all o	•			
		,	able a carcinogenic e	ffect. The table belov	v indicates whet	ner each agency
Sensitization	CAS No	No information availa	able a carcinogenic e	ffect. The table belov	v indicates whet	ner each agency Mexico
Sensitization Carcinogenicity	CAS No 108-88-3	No information availa Limited evidence of a has listed any ingred	able a carcinogenic e ient as a carcino	ffect. The table belov ogen.		

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Toluene	108-88-3	Not listed				
Tetrahydrofuran	109-99-9	Group 2B	Not listed	A3	Х	A3
3-Methoxyphenylmagn esium bromide	36282-40-3	Not listed				

ACGIH: (American Conference of Governmental Industrial A1 - Known Human Carcinogen Hygienists)

Mutagenic Effects

A2 - Suspected Human Carcinogen A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists) Mutagenic effects have occured in microorganisms.

Reproductive Effects	Experiments have shown reproductive toxicity effects on laboratory animals.
Developmental Effects	Developmental effects have occurred in experimental animals.
Teratogenicity	Teratogenic effects have occurred in experimental animals.
STOT - single exposure STOT - repeated exposure	Respiratory system Central nervous system (CNS) Kidney Liver Heart spleen Blood Neurological effects Eyes Ears
Aspiration hazard	No information available
Symptoms / effects,both acute and delayed	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression

Endocrine Disruptor Information

Component	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information		
Tetrahydrofuran	Group III Chemical	Not applicable	Not applicable		
Other Adverse Effects Tumorigenic effects have been reported in experimental animals. The toxicological					
properties have not been fully investigated.					

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Toluene	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50 = 19.7 mg/L 30 min	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)
Tetrahydrofuran	Not listed	2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h	Not listed	EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h

Persistence and Degradability

Immiscible with water

Bioaccumulation/Accumulation

No information available.

Mobility

. Is not likely mobile in the environment due its low water solubility.

Component	log Pow
Toluene	2.73
Tetrahydrofuran	0.45

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Toluene - 108-88-3	U220	-
Tetrahydrofuran - 109-99-9	U213	-

14. Transport information

UN-No	UN2924
Proper Shipping Name	Alcohols,n.o.s., (Ethanol, Methanol)
Technical Name	Toluene, 3-Methoxyphenylmagnesium bromide
Hazard Class	3
Subsidiary Hazard Class	8
Packing Group	II
TDG	
UN-No	UN2924
Proper Shipping Name	Flammable liquid, corrosive, n.o.s.
Hazard Class	3
Subsidiary Hazard Class	8
Packing Group	II
IATA	

UN-No	UN2924
Proper Shipping Name	Flammable liquid, corrosive, n.o.s.
Hazard Class	3
Subsidiary Hazard Class	8
Packing Group	II
IMDG/IMO	
UN-No	UN2924
Proper Shipping Name	Flammable liquid, corrosive, n.o.s.
Hazard Class	3
Subsidiary Hazard Class	8
Packing Group	II
	15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Toluene	108-88-3	Х	ACTIVE	-
Tetrahydrofuran	109-99-9	Х	ACTIVE	-
3-Methoxyphenylmagnesium bromide	36282-40-3	-	-	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Component	CAS No	TSCA 12(b) - Notices of Export
Tetrahydrofuran	109-99-9	Section 4, 1 % de minimus concentration

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Toluene	108-88-3	Х	-	203-625-9	Х	Х	Х	Х	Х	KE-33936
Tetrahydrofuran	109-99-9	Х	-	203-726-8	Х	Х	Х	Х	Х	KE-33454
3-Methoxyphenylmagnesium bromide	36282-40-3	-	-	-	-	-		-	-	-

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	50-60	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	
Toluene	Х	1000 lb	Х	Х	

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors	
Toluene	Х		-	

OSHA - Occupational Safety and Not applicable Health Administration

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Toluene	1000 lb 1 lb	-
Tetrahydrofuran	1000 lb	-

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Toluene	108-88-3	Developmental	-	Developmental
Tetrahydrofuran	109-99-9	Carcinogen	-	Carcinogen

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Toluene	Х	Х	Х	Х	Х
Tetrahydrofuran	Х	Х	Х	-	Х

U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	N
DOT Severe Marine Pollutant	N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Tetrahydrofuran	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
-----------	--------	----------	---------------------------------	------------------------------	--

3-Methoxyphenylmagnesium bromide, 1M solution in THF/toluene

Toluene	108-88-3	Listed	Not applicable	Not applicable	Not applicable
Tetrahydrofuran	109-99-9	Listed	Not applicable	Not applicable	Not applicable
3-Methoxyphenylmagnesium bromide	36282-40-3	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Toluene	108-88-3	Not applicable	Not applicable	Not applicable	Annex I - Y42
Tetrahydrofuran	109-99-9	Not applicable	Not applicable	Not applicable	Not applicable
3-Methoxyphenylmagnesium bromide	36282-40-3	Not applicable	Not applicable	Not applicable	Not applicable

	16. Other information
Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date Revision Date Print Date Revision Summary	19-May-2009 23-Feb-2022 23-Feb-2022 This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS