

SAFETY DATA SHEET

Creation Date 06-Oct-2009 Revision Date 26-Dec-2021 Revision Number 5

1. Identification

Product Name Methylmagnesium iodide, 3M solution in diethyl ether

Cat No.: AC427400000, AC427401000, AC427408000

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids
Category 1
Acute oral toxicity
Category 4
Acute dermal toxicity
Category 4
Acute Inhalation Toxicity - Vapors
Category 4
Skin Corrosion/Irritation
Category 1
Serious Eye Damage/Eye Irritation
Category 1
Specific target organ toxicity (single exposure)
Category 3
Target Organs - Respiratory system, Central nervous system (CNS).

Label Elements

Signal Word

Danger

Hazard Statements

Extremely flammable liquid and vapor

Harmful if swallowed Harmful in contact with skin Harmful if inhaled Causes severe skin burns and eye damage Causes serious eye damage

May cause respiratory irritation. May cause drowsiness and dizziness



Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Response

Call a POISON CENTER or doctor/physician if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Immediately call a POISON CENTER or doctor/physician

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Ingestion

Rinse mouth

Do NOT induce vomiting

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Fire

Explosion risk in case of fire

Fight fire with normal precautions from a reasonable distance

Evacuate area

Storage

Store locked up

Store in a closed container

Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Reacts violently with water

May form explosive peroxides

Repeated exposure may cause skin dryness or cracking

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Ethyl ether	60-29-7	60
Magnesium, iodomethyl-	917-64-6	40

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If

not breathing, give artificial respiration.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media No information available

Flash Point -40 °C / -40 °F

Method - No information available

Autoignition Temperature

Explosion Limits

No information available

Upper
Lower
No data available
No data available
Sensitivity to Mechanical Impact
Sensitivity to Static Discharge
No information available
No information available

Specific Hazards Arising from the Chemical

Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Contact with water liberates extremely flammable gases.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen iodide.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Instability Health Flammability Physical hazards W

Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Uρ

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not expose spill to water.

7. Handling and storage

Handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage.

Corrosives area. Flammables area. Keep away from heat, sparks and flame. Store under an inert atmosphere. Keep away from water or moist air. Protect from light. Store indoors. May form explosive peroxides on prolonged storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Incompatible Materials. Strong oxidizing agents. Strong acids.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl ether	TWA: 400 ppm	(Vacated) TWA: 400 ppm	IDLH: 1900 ppm	TWA: 400 ppm
	STEL: 500 ppm	(Vacated) TWA: 1200 mg/m ³		STEL: 500 ppm
		(Vacated) STEL: 500 ppm		
		(Vacated) STEL: 1500		
		mg/m³		
		TWA: 400 ppm		
		TWA: 1200 mg/m ³		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eve/face Protection Wear appropriate protective eveglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Wear appropriate protective gloves and clothing to prevent skin exposure. Skin and body protection

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

> EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Physical and chemical properties

Physical State Liquid

Appearance No information available Odor No information available **Odor Threshold** No information available

рΗ No information available Melting Point/Range No data available

Boiling Point/Range No information available **Flash Point** -40 °C / -40 °F **Evaporation Rate** No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper No data available No data available Lower **Vapor Pressure** No information available **Vapor Density** No information available 1.26

Specific Gravity

Solubility No information available Partition coefficient; n-octanol/water No data available

Autoignition Temperature No information available

Decomposition Temperature No information available **Viscosity** No information available

Molecular Formula C H3 I Ma 166.24 **Molecular Weight**

10. Stability and reactivity

Yes **Reactive Hazard**

Light sensitive. heat sensitive. Moisture sensitive. Air sensitive. Stability

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to light. Exposure to moist air or water. Exposure to air.

Strong oxidizing agents, Strong acids **Incompatible Materials**

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen iodide

Hazardous polymerization does not occur. **Hazardous Polymerization**

Hazardous Reactions Reacts violently with water.

11. Toxicological information

Acute Toxicity

Product Information

Methylmagnesium iodide, 3M solution in diethyl ether

Oral LD50 Category 4.

Dermal LD50 Category 4. ATE = 1000 - 2000 mg/kg. **Vapor LC50** Category 4. ATE = 10 - 20 mg/l.

Component Information

Component LD50 Oral		LD50 Dermal	LC50 Inhalation		
	Ethyl ether 1215 mg/kg (Rat)		20 mL/kg (Rabbit)	32000 ppm (Rat) 4 h	

Toxicologically Synergistic

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

No information available

Irritation Causes burns by all exposure routes

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Mexico	OSHA	ACGIH	NTP	IARC	CAS No	Component
Not listed	60-29-7	Ethyl ether				
Not listed	917-64-6	Magnesium,				
	Not listed	Not listed	Not listed	Not listed	917-64-6	Magnesium, iodomethyl-

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed

tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and

danger of perforation

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains. .

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl ether	Not listed	LC50: > 10000 mg/L, 96h	EC50 = 5600 mg/L 15 min	EC50 = 165 mg/L/24h
		static (Lepomis macrochirus)	_	_
		LC50: = 2560 mg/L, 96h		
		flow-through (Pimephales		
		promelas)		
		,		

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available.

Mobility .

Component	log Pow
Ethyl ether	0.82

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Ethyl ether - 60-29-7	U117	-

14. Transport information

DOT

UN-No UN3399

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

Technical Name Methylmagnesium iodide, 3M in Diethyl ether

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group 1

TDG

UN-No UN3399

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group |

<u>IATA</u>

UN-No UN3399

Proper Shipping Name Organometalic substance, liquid, water-reactive, flammable (Mixture)

Hazard Class 4.3
Subsidiary Hazard Class 3
Packing Group 1

IMDG/IMO

UN-No UN3399

Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable (Mixture)

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group 1

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Ethyl ether	60-29-7	X	ACTIVE	-
Magnesium, iodomethyl-	917-64-6	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Co	mponent	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
----	---------	--------	-----	------	--------	-------	------	------	------	-------	------

Methylmagnesium iodide, 3M solution in diethyl ether

Ethyl ether	60-29-7	Х	-	200-467-2	Х	Х	Х	Х	Х	KE-27690
Magnesium, iodomethyl-	917-64-6	-	Х	213-031-1	-	-	Х	-	-	-

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs		
Ethyl ether	100 lb	-		

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl ether	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product contains the following DHS chemicals:

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard	
Ethyl ether	Release STQs - 10000lb	

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable
Magnesium, iodomethyl-	917-64-6	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive	Seveso III Directive	Rotterdam	Basel Convention
		(2012/18/EC) -	(2012/18/EC) -	Convention (PIC)	(Hazardous Waste)

		Qualifying Quantities for Major Accident Notification	Qualifying Quantities for Safety Report Requirements		
Ethyl ether	60-29-7	Not applicable	Not applicable	Not applicable	Annex I - Y40 Annex I - Y42
Magnesium, iodomethyl-	917-64-6	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 06-Oct-2009

 Revision Date
 26-Dec-2021

 Print Date
 26-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS