

SAFETY DATA SHEET

Creation Date 29-Jun-2009 Revision Date 28-Dec-2021 Revision Number 5

1. Identification

Product Name sec-Butanol

Cat No.: AC610260000; AC610260010; AC610261000

CAS No 78-92-2

Synonyms sec-Butyl alcohol, 2-Butanol

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number CHEMTREC®, Inside the USA: 800-424-9300

CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Serious Eye Damage/Eye Irritation

Category 2

Specific target organ toxicity (single exposure)

Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

Label Elements

Signal Word

Warning

Hazard Statements

Flammable liquid and vapor Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition/Information on Ingredients

Component	CAS No	Weight %
sec-Butyl alcohol	78-92-2	>95

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

symptoms occur.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention.

Ingestion Do NOT induce vomiting. Get medical attention.

Most important symptoms and

effects

Notes to Physician

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point 24 °C / 75.2 °F

Method - No information available

Autoignition Temperature 390 °C / 734 °F

Explosion Limits

 Upper
 9.8% @ 100°C

 Lower
 1.7% @ 100°C

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Fiammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). peroxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Remove all sources of ignition. Take

precautionary measures against static discharges.

Environmental Precautions Avoid release to the environment. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, **Up** closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on

clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof

equipment. Take precautionary measures against static discharges.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area.

Keep away from heat, sparks and flame. May form explosive peroxides on prolonged storage. Incompatible Materials. Strong oxidizing agents. Acid chlorides. Acid anhydrides.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
sec-Butyl alcohol	TWA: 100 ppm	(Vacated) TWA: 100 ppm	IDLH: 2000 ppm	TWA: 100 ppm
		(Vacated) TWA: 305 mg/m ³	TWA: 100 ppm	
		TWA: 150 ppm	TWA: 305 mg/m ³	
		TWA: 450 mg/m ³	STEL: 150 ppm	
		_	STEL: 455 mg/m ³	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure that eyewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting equipment.

Personal Protective Equipment

Eye/face ProtectionWear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid
Appearance Colorless
Odor sweet

Odor Threshold

pH

No information available
No information available

Melting Point/Range No information available representation available r

Boiling Point/Range 99 °C / 210.2 °F @ 760 mmHg

Flash Point 24 °C / 75.2 °F

Evaporation Rate No information available Flammability (solid,gas) Not applicable

Flammability (solid,gas)
Flammability or explosive limits

 Upper
 9.8% @ 100°C

 Lower
 1.7% @ 100°C

 Vapor Pressure
 17 mbar @ 20 °C

Vapor Density 2.6 Specific Gravity 0.800

Solubility < 12.5 g/1000 ml @ 20 °C

Partition coefficient; n-octanol/waterNo data availableAutoignition Temperature390 °C / 734 °FDecomposition TemperatureNo information available

Viscosity 4.2 mPa.s @ 20 °C

Molecular FormulaC4 H10 OMolecular Weight74.12

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions. May form explosive peroxides on prolonged storage.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

Exposure to light. Exposure to air.

Incompatible Materials Strong oxidizing agents, Acid chlorides, Acid anhydrides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO₂), peroxides

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

 Component
 LD50 Oral
 LD50 Dermal
 LC50 Inhalation

 sec-Butyl alcohol
 2200 mg/kg (Rat)
 > 2 g/kg (Rat)
 49 mg/L (Rat) 4 h (vapour)

 2193 mg/kg (Rat)
 2193 mg/kg (Rat)
 49 mg/L (Rat) 4 h (vapour)

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and respiratory system

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
sec-Butyl alcohol	78-92-2	Not listed				

Mutagenic Effects Not mutagenic in AMES Test

Reproductive Effects

No information available.

Developmental Effects

No information available.

Teratogenicity

No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

delayed

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
sec-Butyl alcohol	Not listed	Pimephales promelas: LC50:	Pseudomonas putida: 500	EC50: 3750 mg/L/24h
		3670 mg/L/96h	mg/L/16h	-

Persistence and Degradability

Soluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation

No information available.

Mobility

. Will likely be mobile in the environment due to its water solubility.

Component	log Pow
sec-Butyl alcohol	0.6

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1120
Proper Shipping Name BUTANOLS

Hazard Class 3
Packing Group III

<u>TDG</u>

UN-No UN1120 Proper Shipping Name BUTANOLS

Hazard Class 3
Packing Group III

<u>IATA</u>

UN-No UN1120
Proper Shipping Name Butanols
Hazard Class 3
Packing Group III

IMDG/IMO

UN-No UN1120
Proper Shipping Name Butanols
Hazard Class 3
Packing Group III

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
sec-Butyl alcohol	78-92-2	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
sec-Butyl alcohol	78-92-2	Х	-	201-158-5	Χ	Χ	Х	Х	Х	KE-03868

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
sec-Butyl alcohol	78-92-2	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA Not applicable

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
sec-Butyl alcohol	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	,	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
sec-Butyl alcohol	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

	Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ī	sec-Butyl alcohol	78-92-2	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities	, ,	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
		for Major Accident Notification	for Safety Report Requirements		
sec-Butyl alcohol	78-92-2	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 29-Jun-2009

 Revision Date
 28-Dec-2021

 Print Date
 28-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS