

SAFETY DATA SHEET

Creation Date 15-Apr-2009 Revision Date 13-Oct-2023 Revision Number 6

1. Identification

Product Name Ethyl ether

Cat No.: E138-1; E138-20; E138-4; E138-4LC; E138-500; E138RS-19;

E138RS-28; E138RS-50

CAS No 60-29-7

Synonyms Ethyl ether; Ether

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 1
Acute oral toxicity Category 4

Specific target organ toxicity (single exposure) Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure) Category 2

Target Organs - Liver.

Aspiration Toxicity Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Extremely flammable liquid and vapor

Extremely flammable liquid and vapor
Harmful if swallowed
May cause respiratory irritation
May cause drowsiness or dizziness
May be harmful if swallowed and enters airways
May cause damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

May form explosive peroxides

Repeated exposure may cause skin dryness or cracking

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Ethyl ether	60-29-7	>95

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get

medical attention.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Notes to Physician

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point -45 °C / -49 °F

Method - No information available

Autoignition Temperature 160 °C / 320 °F

Explosion Limits

 Upper
 36.0 vol %

 Lower
 1.9 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Extremely flammable. Risk of ignition. Vapors may travel to source of ignition and flash back. Vapors may form explosive mixtures with air. Containers may explode when heated. May form explosive peroxides. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2). peroxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

HealthFlammabilityInstabilityPhysical hazards141N/A

6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Remove all sources of ignition. Take

precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Should not be released into the environment. See Section 12 for additional Ecological

Environmental PrecautionsShould not be released into the environment. See Section 12 for add Information.

mormat

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary **Up** measures against static discharges. Keep in suitable, closed containers for disposal. Use

spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Handle under an inert atmosphere. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Do not breathe mist/vapors/spray. Keep away from open flames, hot surfaces and sources of ignition. If peroxide formation is suspected, do not open or move container. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage.

Flammables area. Store under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. May form explosive peroxides. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat, sparks and flame. Keep container tightly closed in a dry and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Strong acids.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Ethyl ether	TWA: 400 ppm	(Vacated) TWA: 400 ppm	IDLH: 1900 ppm	TWA: 400 ppm
	STEL: 500 ppm	(Vacated) TWA: 1200 mg/m ³		STEL: 500 ppm
		(Vacated) STEL: 500 ppm		
		(Vacated) STEL: 1500		
		mg/m³		
		TWA: 400 ppm		
		TWA: 1200 mg/m ³		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations

and safety showers are close to the workstation location. Use explosion-proof

electrical/ventilating/lighting equipment.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: low boiling organic solvent. Type AX. Brown. conforming to EN371.

Hygiene MeasuresHandle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdoraromatic

Odor ThresholdNo information availablepHNo information availableMelting Point/Range-116 °C / -176.8 °FBoiling Point/Range34.6 °C / 94.3 °FFlash Point-45 °C / -49 °F

Evaporation Rate 37.5

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 36.0 vol %

 Lower
 1.9 vol %

Vapor Pressure 587 mbar @ 20 °C

Vapor Density2.55Specific Gravity0.714

SolubilitySlightly soluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature160 °C / 320 °FDecomposition TemperatureNo information available

Viscosity 0.2448 cP at 20 °C Molecular Formula 0.2448 cP at 20 °C C4 H10 O

Molecular FormulaC4 H10 OMolecular Weight74.12

10. Stability and reactivity

Reactive Hazard Yes

Stability May form explosive peroxides. Air sensitive. Light sensitive. Hygroscopic.

Conditions to Avoid Incompatible products. Heat, flames and sparks. Exposure to air. Exposure to light.

Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), peroxides

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions May form explosive peroxides.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component LD50 Oral		LD50 Dermal	LC50 Inhalation		
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm (Rat) 4 h		

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

IrritationNo information availableSensitizationNo information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component CAS No IARC NTP ACGIH OSHA Me

Revision Date 13-Oct-2023 Ethyl ether

Ethyl ether 60-29-7 Not listed Not listed Not listed Not listed Not listed

Mutagenic Effects Mutagenic effects have occurred in experimental animals.

Reproductive Effects No information available.

No information available. **Developmental Effects**

Teratogenicity No information available.

Respiratory system Central nervous system (CNS) STOT - single exposure

STOT - repeated exposure

Aspiration hazard No information available

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl ether	Not listed	LC50: > 10000 mg/L, 96h	EC50 = 5600 mg/L 15 min	EC50 = 165 mg/L/24h
		static (Lepomis macrochirus)	_	_
		LC50: = 2560 mg/L, 96h		
		flow-through (Pimephales		
		promelas)		
		, ,		

Persistence is unlikely based on information available. Persistence and Degradability

Bioaccumulation/ Accumulation No information available.

Will likely be mobile in the environment due to its volatility. **Mobility**

Component	log Pow
Ethyl ether	0.82

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Ethyl ether - 60-29-7	U117	-

14. Transport information

DOT

UN1155 **UN-No Proper Shipping Name** Diethyl ether

Hazard Class 3 **Packing Group**

TDG

UN1155 **UN-No Proper Shipping Name** Diethyl ether

Hazard Class

Packing Group

IATA

UN-No UN1155
Proper Shipping Name UN1155
Diethyl ether

Hazard Class 3
Packing Group

IMDG/IMO

UN-No UN1155
Proper Shipping Name UN1155
Diethyl ether

Hazard Class 3 Packing Group 1

15. Regulatory information

United States of America Inventory

Component	CAS No TSCA		TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Ethyl ether	60-29-7	Χ	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical

Not applicable

Substances & Mixtures, Under TSCA Section 6(h) (PBT)

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

	Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Ī	Ethyl ether	60-29-7	Х	-	200-467-2	X	X	Х	Х	Х	KE-27690

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethyl ether	100 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals.

Revision Date 13-Oct-2023

Ethyl ether

U.S. State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl ether	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Υ **DOT Marine Pollutant** Ν **DOT Severe Marine Pollutant** Ν

U.S. Department of Homeland

This product contains the following DHS chemicals:

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount Security

Component	DHS Chemical Facility Anti-Terrorism Standard
Ethyl ether	Release STQs - 10000lb

Other International Regulations

Mexico - Grade Severe risk, Grade 4

Not applicable Authorisation/Restrictions according to EU REACH

	Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
١	Ethyl ether	60-29-7	-	-	-

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl ether	60-29-7	Not applicable	Not applicable	Not applicable	Annex I - Y40 Annex I - Y42

16. Other information

Regulatory Affairs **Prepared By**

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

Creation Date 15-Apr-2009 **Revision Date** 13-Oct-2023

Print Date

13-Oct-2023

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS