

# SAFETY DATA SHEET

Creation Date 10-Feb-2010 Revision Date 24-Dec-2021 Revision Number 6

# 1. Identification

Product Name Formaldehyde solution, 3.7%-10%

Cat No.: SF96-20; SF98-4; SF98-20

**Synonyms** Formalin solution, 10%-27% (Histological)

Recommended Use Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

### Details of the supplier of the safety data sheet

### Company

Fisher Scientific Company One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

**Emergency Telephone Number** 

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

# 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Category 4 Acute oral toxicity Acute Inhalation Toxicity - Vapors Category 3 Category 2 Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Category 2 Skin Sensitization Category 1 Germ Cell Mutagenicity Category 2 Carcinogenicity Category 1A Specific target organ toxicity (single exposure) Category 1 Target Organs - Optic nerve, Respiratory system, Central nervous system (CNS). Specific target organ toxicity - (repeated exposure) Category 1 Target Organs - Kidney, Liver, spleen, Blood.

#### Label Elements

### Signal Word

Danger

#### **Hazard Statements**

Harmful if swallowed

Causes severe skin burns and eye damage

May cause an allergic skin reaction

Toxic if inhaled

May cause respiratory irritation

May cause drowsiness or dizziness

Suspected of causing genetic defects

May cause cancer

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



### **Precautionary Statements**

#### Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

### Response

Immediately call a POISON CENTER or doctor/physician

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

If skin irritation or rash occurs: Get medical advice/attention

# Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

# Ingestion

Rinse mouth

Do NOT induce vomiting

### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

### Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

#### Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS. WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Water	7732-18-5	84.8 - 94.2
Formaldehyde	50-00-0	3.7 - 10.0
Methyl alcohol	67-56-1	1.0 - 4.1
Odor Mask	NA	0.0 - 1.1

### 4. First-aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

**Inhalation** Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

May cause allergic skin reaction. Difficulty in breathing. . Causes burns by all exposure routes. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

Notes to Physician Treat symptomatically

# 5. Fire-fighting measures

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable Extinguishing Media No information available

Flash Point No information available Method - No information available

**Autoignition Temperature** 

**Explosion Limits** 

No information available

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes.

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2). Formaldehyde. Thermal decomposition can lead to release of irritating gases and

#### vapors.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

HealthFlammabilityInstabilityPhysical hazards310N/A

# 6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Environmental Precautions** 

Should not be released into the environment. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

sewer system. See Section 12 for additional Ecological Information.

**Methods for Containment and Clean** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up** 

	7. Handling and storage
Handling	Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not ingest. If swallowed then seek immediate medical assistance.
Storage.	Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Materials. Strong oxidizing agents.

# 8. Exposure controls / personal protection

### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Formaldehyde	TWA: 0.1 ppm	(Vacated) TWA: 3 ppm	IDLH: 20 ppm	Ceiling: 0.3 ppm
	STEL: 0.3 ppm	(Vacated) STEL: 10 ppm	TWA: 0.016 ppm	
		(Vacated) Ceiling: 5 ppm	Ceiling: 0.1 ppm	
		TWA: 0.75 ppm		
		STEL: 2 ppm		
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm	TWA: 200 ppm
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m <sup>3</sup>	TWA: 200 ppm	STEL: 250 ppm
	Skin	(Vacated) STEL: 250 ppm	TWA: 260 mg/m <sup>3</sup>	
		(Vacated) STEL: 325 mg/m <sup>3</sup>	STEL: 250 ppm	
		Skin	STEL: 325 mg/m <sup>3</sup>	
		TWA: 200 ppm	_	
		TWA: 260 mg/m <sup>3</sup>		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Use only under a chemical fume hood. Ensure adequate ventilation, especially in confined

areas. Ensure that eyewash stations and safety showers are close to the workstation

location.

**Personal Protective Equipment** 

**Eye/face Protection** Tight sealing safety goggles. Face protection shield.

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

**Respiratory Protection** Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorpungent

Odor Threshold
pH

No information available
No information available

Melting Point/Range

Melting Point/Range

0 °C / 32 °F

Boiling Point/Range

100 °C / 212 °F

Flash Point

No information available

Evaporation Rate

No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

UpperNo data availableLowerNo data availableVapor PressureNo information available

Vapor Density> 1.00Specific Gravity> 1.00Solubilitymiscible

Partition coefficient; n-octanol/waterNo data availableAutoignition TemperatureNo information availableDecomposition TemperatureNo information availableViscosityNo information available

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat.

Incompatible Materials Strong oxidizing agents

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Formaldehyde, Thermal decomposition can

lead to release of irritating gases and vapors

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

# 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

Oral LD50 Category 4. ATE = 300 - 2000 mg/kg.

**Dermal LD50** Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50 Category 3. ATE = 2 - 10 mg/l.

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	-	ı	-
Formaldehyde	500 mg/kg (Rat)	LD50 = 270 mg/kg (Rabbit)	0.578 mg/L (Rat) 4 h
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L ( Rat ) 4 h

**Toxicologically Synergistic** 

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes, respiratory system and skin

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Water	7732-18-5	Not listed				
Formaldehyde	50-00-0	Group 1	Known	A1	X	A2
Methyl alcohol	67-56-1	Not listed				
Odor Mask	NA	Not listed				

IARC (International Agency for Research on Cancer)

NTP: (National Toxicity Program)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human

Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen A2 - Suspected Human Carcinogen A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen A5 - Not Suspected as a Human Carcinogen

**Mutagenic Effects** Mutagenic effects have occurred in humans.

**Reproductive Effects** Experiments have shown reproductive toxicity effects on laboratory animals.

**Developmental Effects** Developmental effects have occurred in experimental animals.

**Teratogenicity** Teratogenic effects have occurred in experimental animals.

Optic nerve Respiratory system Central nervous system (CNS) STOT - single exposure

STOT - repeated exposure Kidney Liver spleen Blood

**Aspiration hazard** No information available

delayed

Symptoms / effects, both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

**Endocrine Disruptor Information** No information available

Other Adverse Effects Tumorigenic effects have been reported in experimental animals. See actual entry in

RTECS for complete information.

# 12. Ecological information

#### **Ecotoxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Formaldehyde	Not listed	Leuciscus idus: LC50 = 15	Not listed	EC50 = 20 mg/L 96h
		mg/L 96h		EC50 = 2  mg/L  48h
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
_		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	
			EC50 = 43000 mg/L 5 min	

**Persistence and Degradability** 

Miscible with water Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** 

No information available.

**Mobility** 

. Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Formaldehyde	-0.35
Methyl alcohol	-0.74

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Formaldehyde - 50-00-0	U122	-
Methyl alcohol - 67-56-1	U154	=

# 14. Transport information

DOTNot regulatedTDGNot regulatedIATANot regulatedIMDG/IMONot regulated

# 15. Regulatory information

### **United States of America Inventory**

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Water	7732-18-5	X	ACTIVE	-
Formaldehyde	50-00-0	X	ACTIVE	-
Methyl alcohol	67-56-1	Х	ACTIVE	-
Odor Mask	NA	-	-	-

### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

TSCA 12(b) - Notices of Export

Not applicable

### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Water	7732-18-5	Х	-	231-791-2	Х	Х		Х	Х	KE-35400
Formaldehyde	50-00-0	Х	-	200-001-8	Χ	Χ	Χ	Х	Х	KE-17074
Methyl alcohol	67-56-1	Χ	-	200-659-6	Χ	Χ	Χ	Х	Χ	KE-23193
Odor Mask	NA	-	-	-	-	-		-	-	-

<sup>&#</sup>x27;-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

### U.S. Federal Regulations

#### **SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Formaldehyde	50-00-0	3.7 - 10.0	0.1
Methyl alcohol	67-56-1	1.0 - 4.1	1.0

### SARA 311/312 Hazard Categories See section 2 for more information

**CWA (Clean Water Act)** 

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Formaldehyde	X	100 lb	-	-

### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Formaldehyde	X		-
Methyl alcohol	X		-

# **OSHA** - Occupational Safety and Health Administration

Component	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Formaldehyde	2 ppm STEL	TQ: 1000 lb
<b>1</b>	0.5 ppm Action Level	
	0.75 ppm TWA	

# CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Formaldehyde	100 lb	100 lb
Methyl alcohol	5000 lb	-

### **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Formaldehyde	50-00-0	Carc. (Gaseous only)	40 μg/day	Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental

# U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Water	-	-	X	-	-
Formaldehyde	X	X	X	X	X
Methyl alcohol	X	X	X	X	X

### **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

# U.S. Department of Homeland

Security

This product contains the following DHS chemicals:

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard		
Formaldehyde	Release STQs - 15000lb (solution)		

### Other International Regulations

Mexico - Grade No information available

### Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Formaldehyde	-	Use restricted. See item 72. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Methyl alcohol	-	Use restricted. See item 69. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Water	7732-18-5	Listed	Not applicable	Not applicable	Not applicable
Formaldehyde	50-00-0	Listed	Not applicable	Not applicable	Not applicable
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable
Odor Mask	NA	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Water	7732-18-5	Not applicable	Not applicable	Not applicable	Not applicable
Formaldehyde	50-00-0	5 tonne	50 tonne	Not applicable	Not applicable
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable
Odor Mask	NA	Not applicable	Not applicable	Not applicable	Not applicable

# 16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 10-Feb-2010

 Revision Date
 24-Dec-2021

 Print Date
 24-Dec-2021

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# **End of SDS**