

# **SAFETY DATA SHEET**

Creation Date 15-Apr-2009 Revision Date 24-Dec-2021 Revision Number 5

1. Identification

Product Name Diethyl ether

Cat No.: AC176820000, AC176820010, AC176820025, AC176820050,

AC176820250

**CAS No** 60-29-7

Synonyms Ethyl ether; Ether

Recommended Use Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

## Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

# 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 1
Acute oral toxicity Category 4

Specific target organ toxicity (single exposure)

Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure)

Category 2

Target Organs - Liver.

Aspiration Toxicity Category 1

## Label Elements

## Signal Word

Danger

#### **Hazard Statements**

Extremely flammable liquid and vapor Harmful if swallowed May cause respiratory irritation May cause drowsiness or dizziness May be harmful if swallowed and enters airways

May cause damage to organs through prolonged or repeated exposure



# **Precautionary Statements**

# Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

#### Response

Get medical attention/advice if you feel unwell

#### Inhalatior

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

# Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

# **Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

# **Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

May form explosive peroxides

Repeated exposure may cause skin dryness or cracking

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Ethyl ether	60-29-7	>95

# 4. First-aid measures

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get

medical attention.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

**Notes to Physician** 

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

# 5. Fire-fighting measures

Suitable Extinguishing Media CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point -45 °C / -49 °F

Method - No information available

Autoignition Temperature 160 °C / 320 °F

**Explosion Limits** 

 Upper
 36.0 vol %

 Lower
 1.9 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

## Specific Hazards Arising from the Chemical

Extremely flammable. Risk of ignition. Vapors may travel to source of ignition and flash back. Vapors may form explosive mixtures with air. Containers may explode when heated. May form explosive peroxides. Vapors may form explosive mixtures with air.

### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2). peroxides.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

HealthFlammabilityInstabilityPhysical hazards141N/A

## 6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Remove all sources of ignition. Take

precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

**Environmental Precautions** Should not be released into the environment. See Section 12 for additional Ecological

Information.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary

Up

measures against static discharges. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

# 7. Handling and storage

Handling

Wear personal protective equipment/face protection. Handle under an inert atmosphere. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Do not breathe mist/vapors/spray. Keep away from open flames, hot surfaces and sources of ignition. If peroxide formation is suspected, do not open or move container. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage.

Flammables area. Store under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. May form explosive peroxides. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat, sparks and flame. Keep container tightly closed in a dry and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Strong acids.

# 8. Exposure controls / personal protection

## **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl ether	TWA: 400 ppm	(Vacated) TWA: 400 ppm	IDLH: 1900 ppm	TWA: 400 ppm
	STEL: 500 ppm	(Vacated) TWA: 1200 mg/m <sup>3</sup>		STEL: 500 ppm
		(Vacated) STEL: 500 ppm		
		(Vacated) STEL: 1500		
		mg/m³		
		TWA: 400 ppm		
		TWA: 1200 mg/m <sup>3</sup>		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations

and safety showers are close to the workstation location. Use explosion-proof

electrical/ventilating/lighting equipment.

Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdoraromatic

Odor ThresholdNo information availablepHNo information availableMelting Point/Range-116 °C / -176.8 °FBoiling Point/Range34.6 °C / 94.3 °FFlash Point-45 °C / -49 °F

Evaporation Rate 37.5

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 36.0 vol %

 Lower
 1.9 vol %

Vapor Pressure 587 mbar @ 20 °C

Vapor Density2.55Specific Gravity0.714

SolubilitySlightly soluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature160 °C / 320 °FDecomposition TemperatureNo information available

Viscosity0.2448 cP at 20 °CMolecular FormulaC4 H10 O

Molecular Formula C4 H10 O
Molecular Weight 74.12

# 10. Stability and reactivity

Reactive Hazard Yes

**Stability** May form explosive peroxides. Air sensitive. Light sensitive. Hygroscopic.

Conditions to Avoid Incompatible products. Heat, flames and sparks. Exposure to air. Exposure to light.

Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), peroxides

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** May form explosive peroxides.

# 11. Toxicological information

**Acute Toxicity** 

Product Information

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm (Rat) 4 h

Toxicologically Synergistic No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

IrritationNo information availableSensitizationNo information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

- 1	_						
- 1	Component	CAS No	IARC	l NTP	ACGIH	OSHA	l Mexico
- 1	••••••••	07.0				• • • • • • • • • • • • • • • • • • • •	

Ethyl ether 60-29-7 Not listed Not listed Not listed Not listed Not listed

Mutagenic Effects Mutagenic effects have occurred in experimental animals.

**Reproductive Effects** No information available.

No information available. **Developmental Effects** 

**Teratogenicity** No information available.

Respiratory system Central nervous system (CNS) STOT - single exposure

STOT - repeated exposure

**Aspiration hazard** No information available

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

Other Adverse Effects See actual entry in RTECS for complete information.

# 12. Ecological information

#### **Ecotoxicity**

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl ether	Not listed	LC50: > 10000 mg/L, 96h	EC50 = 5600 mg/L 15 min	EC50 = 165 mg/L/24h
		static (Lepomis macrochirus)	_	_
		LC50: = 2560 mg/L, 96h		
		flow-through (Pimephales		
		promelas)		
		, ,		

Persistence is unlikely based on information available. Persistence and Degradability

**Bioaccumulation/ Accumulation** No information available.

Will likely be mobile in the environment due to its volatility. **Mobility** 

Component	log Pow
Ethyl ether	0.82

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Ethyl ether - 60-29-7	U117	-

# 14. Transport information

DOT

UN1155 **UN-No Proper Shipping Name** Diethyl ether

**Hazard Class** 3 **Packing Group** 

**TDG** 

UN1155 **UN-No Proper Shipping Name** Diethyl ether

**Hazard Class** 

Packing Group

<u>IATA</u>

UN-No UN1155
Proper Shipping Name UN1155
Diethyl ether

Hazard Class 3
Packing Group 1

IMDG/IMO

UN-No UN1155
Proper Shipping Name UN1155
Diethyl ether

Hazard Class 3
Packing Group

# 15. Regulatory information

## **United States of America Inventory**

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Ethyl ether	60-29-7	Χ	ACTIVE	-

#### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

## **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Ethyl ether	60-29-7	Х	-	200-467-2	X	X	Х	Х	Х	KE-27690

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** - Occupational Safety and

Health Administration

Not applicable

**CERCLA** This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethyl ether	100 lb	-

**California Proposition 65** 

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know

Regulations

	Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Г	Ethyl ether	X	X	X	=	X

## **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### U.S. Department of Homeland

This product contains the following DHS chemicals:

**Security** Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard
Ethyl ether	Release STQs - 10000lb

## **Other International Regulations**

Mexico - Grade Severe risk, Grade 4

Authorisation/Restrictions according to EU REACH

## Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable
Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl ether	60-29-7	Not applicable	Not applicable	Not applicable	Annex I - Y40 Annex I

16	Other	inform	ation

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 15-Apr-2009

 Revision Date
 24-Dec-2021

 Print Date
 24-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

- Y42

Harmonized System of Classification and Labeling of Chemicals (GHS).

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# **End of SDS**